

imageRUNNER ADVANCE



imageRUNNER ADVANCE 715iF III Series

Black-and-White | Compact | Multifunction

Print up to 75 ppm (BW)

Scan up to 100 ipm (300 dpi) (BW/color, duplex)

Print up to 8-1/2" x 14"

3,300-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology; better **control** sensitive information and print-related costs; and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive and Box.¹
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM* systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control² utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.³

QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.





- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally-conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR[®] certified and rated EPEAT[®] Gold.⁴

CONFIGURATION OPTIONS



SPECIFICATIONS

Main Unit

Туре

Monochrome Laser Multifunction

Core Functions Print, Copy, Scan, Send, Fax

Processor

Canon Dual Custom Processor (Shared) **Control Panel**

10.1" WSVGA Color Touch-panel

Memory

3.0 GB RAM

Hard Disk Drive 250 GB

Interface Connection

1000Base-T/100Base-TX/10Base-T, Network Wireless LAN (IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Low Energy Others Standard USB 2.0 x2 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device) Copy Control Interface Optional:

Paper Capacity (LTR, 20 lb. Bond) Standard: 650 Sheets 3,300 Sheets Maximum

Paper Sources (LTR, 20 lb. Bond)

550-sheet Paper Cassette, 100-sheet Stack Standard: **Bypass** Optional: 550-sheet (CASSETTE FEEDING UNIT-AR1), 2,650-sheet (HIGH CAPACITY CASSETTE FEEDING UNIT-D1), 550-sheet (CASSETTE MODULE-AG1), 75-envelope (ENVELOPE CASSETTE MODULE-A1)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard Model: 500 Sheets Finisher Model: 1,000 Sheets

Finishing Capabilities

Standard Model: Collate, Group Finisher Model: Collate, Group, Offset, Staple

Supported Media Types

Cassettes:	Thin, Plain, Recycled, Color, Heavy,
	Labels, Bond, Pre-punched
Stack Bypass:	Thin, Plain, Recycled, Color, Heavy,
	Transparency, Bond, Envelope

Supported Media Sizes

Cassette (Std.):	Letter, Executive, Statement, Custom size
	(3-7/8" x 5-7/8" to 8-1/2" x 11-3/4")
Cassettes (Opt.):	Legal, Letter, Executive, Statement,
	Custom size (3-7/8" x 5-7/8" to 8-1/2 x 14")
Stack Bypass:	Legal, Letter, Executive, Statement,
	Envelope [No.10 (COM10), Monarch,
	DL, ISO-C5], Custom size (3" x 5" to
	8-1/2" x 14")

Supported Media Weights

Cassette:	16 lb. Bond to 36 lb. Bond (60 to 135 g/m ²)	
Stack Bypass:	16 lb. Bond to 74 lb. Cover (60 to 199 g/m ²)	
Duplex:	16 lb. Bond to 32 lb. Bond (60 to 120 g/m ²)	
Print/Copy Speed (BW)		
715iF III/715iFZ III: Up to 75 ppm (Letter);		
	Up to 59 ppm (Legal)	
	Up to 65 ppm (Lattor):	

615iF III/615iFZ III:	Up to 65 ppm (Letter);	
	Up to 51 ppm (Legal)	
525iF III/525iFZ III:	Up to 55 ppm (Letter);	
	Up to 45 ppm (Legal)	
Warm-up Time		
From Power On: 3	80 Seconds or Less⁵	
From Sleep		
Mode:	10 Seconds or Less ⁶	
Quick Startup		
Mode:	4 Seconds or Less ⁷	
Dimensions (W x D x H)		
Standard Model: 2	20-1/4" x 23-5/8" x 24-1/4"	
	(513 mm x 601 mm x 617 mm)	
Finisher Model:	20-1/4" x 23-5/8" x 32-1/8"	
	(513 mm x 601 mm x 814 mm)	

Dimensions (W x D x H) with Paper Feeding Unit or High Capacity Paper Feeding

Standard Model: 25-1/4" x 26-3/8" x 42-1/4" (642 mm x 668 mm x 1073 mm) 25-1/4" x 26-3/8" x 50" Finisher Model: (642 mm x 668 mm x 1270 mm)

Installation Space (W x D) 41-3/8" x 32-3/8" (1,052 mm x 823 mm)

Weight⁸ Standard Model: Approx. 81.6 lb. (37 kg) Finisher Model: Approx. 101.4 lb. (46 kg)

Print Specifications

Print Resolution (dpi) 1200 x 600 Standard Page Description Languages UFR II, PCL[®]6, Adobe[®] PS[®] 3

Direct Print

Available from USB, Advanced Box, Remote UI, and Web Access⁹

Supported File Types

PDF. TIFF. JPEG. EPS. XPS

Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from compatible mobile devices or Internet-connected devices and cloud-based services depending on your requirements.¹⁰

Fonts	
PCL fonts:	93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese,
	Korean, Simplified and Traditional Chines
	Barcode Fonts ¹²
PS fonts:	136 Roman

On

E

UFRII/PS:	Windows® 7/8.1/10, Windows Server 2008/2008 R2/2012/2012 R2/2016,
	MAC OS X (10.9 or later)
PCL:	Windows® 7/8.1/10, Windows Server
	2008/2008 R2/2012/2012 R2/2016
PPD:	Windows® 7/8.1/10, MAC OS X (10.3.9
	or later)

Copy Specifications

First-Copy-Out Time (LTR) As fast as 5 Seconds Copy Resolution (dpi) 600 x 600 **Multiple Copies**

Up to 9,999 Magnification

25%-400% (1% Increments) Preset Reductions

25%, 50%, 64%, 78% Preset Enlargements

129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Two-sided Original, Finishing, Job Build, N on 1, Different Size Originals,14 Density Adjustment, Original Type Selection, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Job Done Notice, Copy ID Card, Skip Blank Pages, Multi Sheet Feed Detection

Scan Specifications

Type

Single-pass Duplexing Automatic Document Feeder¹⁵ Document Feeder Paper Capacity

100 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes Legal, Letter, Statement

Custom size: 4-1/8" x 5-7/8" to 8-1/2" x 14"

Document Feeder Supported Media Weights 12 lb. Bond to 33 lb. Bond (42 to 128 g/m²) BW Original:

Color Original: 17 lb. Bond to 33 lb. Bond (64 to 128 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height up to 1-1/4"; Weight Up to 4.4 lb. (2 kg)]

Pull Scan

Color Network ScanGear2 for both Twain and WIA Supported OS: Windows 7/8.1/10/ Server 2008/Server 2008 R2/ Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices or cloud-based services depending on your requirements.

Scan Speed (LTR)

Single-sided Scanning	
Color/BW:	50 ipm/50 ipm (300 dpi, send)
BW:	50 ipm (600 dpi, copy)
Double-sided Scanning	
Color/BW:	100 ipm/100 ipm (300 dpi, send)
BW:	100 ipm (600 dpi, copy)

Send Specifications

Destination

Standard:	Email/Internet Fax (SMTP), SMB, FTP,
	WebDAV, Mail Box, Super G3 Fax
Optional	IP Fax

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Communication Protocol

File:	FTP (TCP/IP), SMB v3.0, WebDAV
Email:	SMTP, POP3
File Format	

Sta

Opt

indard:	TIFF, JPEG, PDF (Compact, Searchable,
	Apply Policy, Optimize for Web, PDF
	A/1-b, Encrypted, Device Signature), XPS
	(Compact, Searchable, Device Signature),
	Office Open XML (PowerPoint®, Word)
tional:	PDF (Trace & Smooth, User Signature), XPS
	(User Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Different-size Originals,¹⁴ Density Adjustment, Sharpness, Erase Frame, Job Build, Sender's Name (TTI), Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-To, Email Priority, TX Report, Original Content Orientation, Skip Blank Pages, Multi Sheet Feed Detection

L TOILS.	55 Noman, 10 Ditinap roms, 2 OCN roms,
	Andalé Mono WT J/K/S/T (Japanese,
	Korean, Simplified and Traditional Chinese),"
	Barcode Fonts ¹²
fonts:	136 Roman
erating System ¹³	

Fax Specifications

Maximum Number of Connection Lines One Modem Speed Super G3: 33.6 Kbps G3: 14.4 Kbps Compression Method MH, MR, MMR, JBIG

Resolution (dpi) 400 × 400, 200 × 400, 200 × 200, 200 × 100

Sending/Recording Size Statement to Legal

Fax Memory Up to 30,000 Pages

Speed Dials Max. 200

Group Dials/Destinations Max. 199 Dials

Sequential Broadcast Max. 256 Addresses

Memory Backup

Yes

Fax Features

Original Type Selection, Two-sided Original, Density for Scanning, Sharpness, Erase Frame, Job Build, Sender's Name (TTI), Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

Store Specifications

Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows 7/8.1/10) Concurrent Connections (Max.) SMB: 64 WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space Approx. 16 GB

Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media Standard: USB

Security Specifications

Authentication

 Standard:
 Universal Login Manager (Device and Function Level Log-in), User Authentication, Department ID Authentication, Access Management System, uniFLOW Online Express¹⁶

 Optional:
 uniFLOW

Data Standard:

Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup, McAfee Embedded Control² IEEE 2600 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network Standard:

Optional:

IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

 Standard:
 Secure Print, Adobe LiveCycle® Rights

 Management ES2.5 Integration, Encrypted

 PDF, Encrypted Secure Print, Device

 Signature, Secure Watermark

 Optional:
 User Signature

Environmental Specifications

Operating Environment Temperature: 50 to 86° F

Humidity: 20 to 80% RH (Relative Humidity)
Power Requirements

120-127V, 60 Hz, 9.7 A Plug (Main Unit)

NEMA 5-15P

Power Consumption

Maximum: Approx. 1,500 W Approx. 29.77 W17 Standby: Sleep Mode: Approx. 1.0 W¹⁸ Typical Electricity Consumption (TEC) Rating¹⁹ 715iF III: Ó.82 kWh 715iFZ III: 0.83 kWh 615iF III: 0.68 kWh 615iFZ III: 0.69 kWh 525iF III/525iFZ III: 0.58 kWh

Standards

ENERGY STAR[®] Certified Rated EPEAT[®] Gold⁴

Consumables

Toner

T03 Black (All-in-One Toner Cartridge)²⁰

Toner Yield²¹

51,500 Images

- ¹ Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions. ² Requires Unified Firmware Platform v3.9.
- ³ Requires additional option
- ⁴ For current EPEAT rating (Gold/Silver/Bronze),
- please visit www.epeat.net.
- ⁵ Time from device power-on until copy ready (not print
- reservation). ⁶ Time from exiting sleep mode to when printing is operational.
- ⁷ Time from device power-on to when copy icon appears on the main menu of touch-panel.
- ⁸ Includes consumables.
- ⁹ PDF print from Web sites is supported.
- ¹⁰ For more information, including compatibility, please visit https://www.usa.canon.com/mobile-app.
 ¹¹ Requires the optional PCL International Font Set-A1.
- Requires the optional PCL International Font Second PCL International Font Second Printer Kit-D1.
- ³ Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- ¹⁴ Only for Letter/Legal.
- ¹⁵ Detect Feeder Multi Sheet Feed is supported.
- ¹⁶ No charge for this solution; however activation is required.
 ¹⁷ Reference value (measured one unit).
- ¹⁸ 1.0 W sleep mode not available in all circumstances due to certain settings.
- due to certain settings. ¹⁹ Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.
- ²⁰ Includes toner, drum, developer, and waste toner hopper.
- ²¹ Toner cartridge yield in accordance with ISO/IEC 19752.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE 715iF III Series Specifications document.



As an ENERGY STAR[®] Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of trademarks of trademarks under the direct trademarks or trademarks or trademarks of the Countries. CUSA, through its subsidiary CIIS, has strategic partnerships with Box and mxHero. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. McAfee and the McAfee logo are trademarks of McAfee LLC in the US and/or other countries. All other referenced in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Solutions America Sales Representative for details. Products shown with optional accessories. Canon U.S.A. and Canon Solutions America do not provide legal counsel or regulatory compliance consultarcy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typogr

CSA-19-285 1019R2-CSAiRA715iFIIISB-PDF-IH







To learn about Canon's many awards, visit ess.csa.canon.com/awards.