

imageRUNNER ADVANCE C475iF III Series

Color | Compact | Multifunction

Print up to 50 ppm (BW/color)

Scan up to 100 ipm (300 dpi) (BW/color, duplex)

Print up to 8-1/2" × 14"

2,300-sheet maximum paper capacity



Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive!
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM* systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control² utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.³



QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V² color profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.

* Security Information and Event Management





DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold⁴

CONFIGURATION OPTIONS

imageRUNNER ADVANCE C475iF III*
(Standard Model)



imageRUNNER ADVANCE C475iFZ III
(Finisher Model)



CASSETTE FEEDING UNIT-ASI

- 550-sheet capacity and cabinet for storage
- Supports up to Legal
- Supports 16 lb. Bond to 60 lb. Cover



CASSETTE FEEDING UNIT-ATI

- 1,650-sheet capacity
- Supports up to Legal
- Supports 16 lb. Bond to 60 lb. Cover



CASSETTE MODULE-AJ1**

- Desktop configuration
- 550-sheet capacity
- Supports up to Legal
- Supports 16 lb. Bond to 60 lb. Cover

*Finisher cannot be added after purchase.

**Can add up to two additional cassettes.

SPECIFICATIONS

Main Unit

Type

Color Laser Multifunctional

Core Functions

Print, Copy, Scan, Send, Store, Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

Memory

4.0 GB RAM

Hard Disk Drive

250 GB

Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,
Wireless LAN (IEEE 802.11 b/g/n)

Optional: NFC, Bluetooth Low Energy

Others

Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)

Optional: Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 650 Sheets

Maximum: 2,300 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: 550-sheet Paper Cassette, 100-sheet Stack
Bypass

Optional: 1,650-sheet Paper Cassette
(Cassette Feeding Unit-AT1)
550-sheet Paper Cassette
(Cassette Feeding Unit-AS-1)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard

Model: 400 Sheets

Finisher: 900 Sheets (400 sheets: base tray, 400

Model: sheets: upper tray, 100 sheets: lower tray)

Finishing Capabilities

Standard

Model: Collate, Group

Finisher

Model: Collate, Group, Offset, Staple

Supported Media Types

Stack Bypass: Thin, Plain, Recycled, Heavy, Color, Bond,
Envelope

Cassette: Thin, Plain, Recycled, Heavy, Color, Label,
Bond

Supported Media Sizes

Stack Bypass: Legal, Letter, Executive, Statement,
Envelopes [No.10 (COM10), Monarch, DL,
ISO-C5], Custom size: 3" x 5" to 8-1/2" x 14"
(76 x 127 mm to 215.9 mm x 355.6 mm)

Cassette: Legal, Letter, Executive, Statement,
Custom Size: 4" x 5-7/8" to 8-1/2" x 14"
(101.6 mm x 148 mm to 215.9 mm x 355.6 mm)

Supported Media Weights

Cassettes: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m²)

Stack Bypass: 16 lb. Bond to 80 lb. Cover (60 to 216 g/m²)

Duplex: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m²)

Print/Copy Speed (BW and Color)

C475iF III / Up to 50 (Letter), Up to 39 (Legal)

C475iFZ III:

Warm-up Time

From Power On: Approx. 10 Seconds⁵

From Sleep: Approx. 10 Seconds⁵

Mode:

Quick Startup: Approx. 4 Seconds⁷

Mode:

Dimensions (W x D x H)

Standard: 20-1/2" x 25-3/8" x 26-3/8"

Model: (521 mm x 645 mm x 668 mm)

Finisher: 20-1/2" x 25-3/8" x 34"

Model: (521 mm x 645 mm x 864 mm)

Dimensions (W x D x H) with Paper Feeding Unit

Standard Model: 25-1/4" x 26-3/8" x 44-1/4"
(642 mm x 668 mm x 1124 mm)

Finisher Model: 25-1/4" x 26-3/8" x 52"
(642 mm x 668 mm x 1320 mm)

Installation Space (W x D)

37-3/8" x 33-1/8" (950 mm x 840 mm)

Weight⁸

Standard

Model: Approx. 101.4 lb. (46 kg)

Finisher Model: Approx. 121.3 lb. (55 kg)

Print Specifications

Print Resolution (dpi)

1200 x 600

Standard Page Description Languages

UFR II, PCL⁶, Adobe[®] PS[®] 3

Direct Print

Available from USB, Advanced Box, Remote UI,
and Web Access⁹

Supported File Types

PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available
to provide printing from mobile devices or Internet-
connected devices and cloud-based services depending on
your requirements.¹⁰

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T (Japanese,
Korean, Simplified and Traditional Chinese),¹¹
Barcode Fonts¹²

PS fonts: 136 Roman

Operating System¹³

UFR II/PS: Windows[®] 7/8.1/10, Windows Server 2008/
2008 R2/2012/2012 R2/2016, MAC OS X
(10.9 or later)

PCL: Windows 7/8.1/10, Windows Server
2008/2008 R2/2012/2012 R2/2016

PS: Windows 7/8.1/10, Windows Server
2008/2008 R2/2012/2012 R2/2016,
MAC OS X (10.9 or later)

PPD: Windows 7/8.1/10, MAC OS X (10.3.9 or later)

Copy Specifications

First-Copy-Out Time (LTR)

C475iF III/
C475iFZ III:

As Fast as 5.1/5.8 Seconds

Copy Resolution (dpi)

600 x 600

Multiple Copies

Up to 9,999

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 78%

Preset Enlargements

129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper
Setting, Previous Settings, Favorite Settings, Finishing,
Two-sided, Density Adjustment, Original Type Selection,
Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Two-sided Original, Finishing, Job Build, N on 1, Different Size
Originals,¹⁴ Density Adjustment, Original Type Selection, Page
Numbering, Copy Set Numbering, Sharpness, Erase Frame,
Secure Watermark, Print Date, Shift, Job Done Notice, Copy
ID Card, Skip Blank Pages, Multi-Sheet Feed Detection,
Adjust One-Touch Color, Color Balance

Scan Specifications

Type

Single-pass Duplexing Automatic Document Feeder¹⁵

Document Feeder Paper Capacity

100 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

Legal, Letter, Statement, Custom Size: 4-1/8" x 5-7/8" to
8-1/2" x 14" (105 mm x 148 mm to 216 mm x 355.6 mm)

Document Feeder Supported Media Weights

BW Original: 1-sided scanning: 12 to 33 lb. Bond
(42 to 128 g/m²)

2-sided scanning: 13 to 33 lb. Bond
(50 to 128 g/m²)

CL Original: 1-sided scanning: 17 to 33 lb. Bond
(64 to 128 g/m²)

2-sided scanning: 17 to 33 lb. Bond
(64 to 128 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: Up to 1-1/4"
(30 mm), Weight: Up to 4.4 lb. (2kg)]

Pull Scan

Color Network ScanGear2 for both Twain and WIA

Supported OS: Windows 7/8.1/10/
Server 2008/Server 2008 R2/
Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,
200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to
mobile devices and cloud-based services depending on
your requirements.

Scan Speed (LTR)

Single-sided Scanning (BW and Color):

50 ipm (300 dpi)/30 ipm (600 dpi)

Double-sided Scanning (BW and Color):

100 ipm (300 dpi)/50 ipm (600 dpi)

Send Specifications

Destination

Standard: Email/Internet Fax (SMTP),
SMB v3.0, FTP, WebDAV, Mail
Box, Super G3 Fax
IP Fax

Optional:

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,
200 x 100, 150 x 150, 100 x 100

Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV

Email: SMTP, POP3

File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable,
Apply policy, Optimize for Web, PDF
A/1-b, Encrypted, Device Signature), XPS
(Compact, Searchable, Device Signature),
Office Open XML (PowerPoint, Word)

Optional: PDF (Trace & Smooth, User Signature), XPS
(User Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Different-size
Originals,¹⁴ Density Adjustment, Sharpness, Erase Frame, Job
Build, Sender's Name (TTI), Delayed Send, Preview, Job Done
Notice, File Name, Subject/Message, Reply-to, Email Priority,
TX Report, Original Content Orientation, Skip Blank Pages,
Multi-Sheet Feed Detection

Fax Specifications

Maximum Number of Connection Lines

1

Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending and Recording Size

Statement to Recording

Fax Memory

Up to 30,000 Pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup

Yes

Fax Features

Original Type Selection, Two-sided Original, Density for Scanning, Sharpness, Erase Frame, Job Build, Sender's Name (TTI), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

Store Specifications

Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV Supported

Client PC: Windows 7/8.1/10

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB

Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media

Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager (Device and Function Level Log-in), uniFLOW Online Express,¹⁶ User Authentication, Department ID Authentication, Access Management System

Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup, McAfee Embedded Control²

Optional: IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network

Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature, Secure Watermark

Optional: User Signatures

Environmental Specifications

Operating Environment

Temperature: 50 to 86 °F

Humidity: 20 to 80 % RH (Relative Humidity)

Power Requirements

120-127V AC 60 Hz, 8.4 A

Plug (Main Unit)

NEMA 5-15P

Power Consumption

Maximum: Approx. 1,500 W

Standby: Approx. 54.3 W¹⁷

Sleep Mode: Approx. 1.0 W¹⁸

Typical Electricity Consumption (TEC) Rating¹⁹
0.54 kWh

Standards

ENERGY STAR® Certified

Rated EPEAT® Gold⁴

Consumables

Toner Cartridge

TONER T04 BK/C/M/Y

Toner Yield

TONER T04 BK: 33,000 pages²⁰

TONER T04

C/M/Y: 27,500 pages²⁰

¹ Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.

² Requires Unified Firmware Platform v3.9.

³ Requires additional option.

⁴ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.

⁵ Time from device power-on, until copy ready (not print reservation).

⁶ Time from exiting Sleep mode to when printing is operational.

⁷ Time from device power-on to when copy jobs can be programmed.

⁸ Includes consumables.

⁹ PDF print from Web sites is supported.

¹⁰ For more information, including compatibility, please visit <https://www.usa.canon.com/mobile-app>.

¹¹ Requires the optional PCL International Font Set-A1.

¹² Requires the optional Barcode Printer Kit-D1.

¹³ Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

¹⁴ Only for Letter/Legal.

¹⁵ Detect Feeder Multi Sheet Feed is supported.

¹⁶ No charge for this solution; however activation is required.

¹⁷ Reference value (measured one unit).

¹⁸ 0.8 W sleep mode not available in all circumstances due to certain settings.

¹⁹ Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

²⁰ Toner Cartridge yield in accordance with ISO/IEC 19798.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE C475iF III Series Specifications document.



For more information, call or visit
1.800.815.4000 CSA.CANON.COM



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. McAfee and the McAfee logo are trademarks of McAfee LLC in the US and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Solutions America Sales Representative for details. Products shown with optional accessories. Canon U.S.A. and Canon Solutions America do not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2019 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



To learn about Canon's many awards, visit
ess.csa.canon.com/awards.