



HP PageWide XL High-capacity Stacker

High-capacity output solution specially designed to keep up
with HP PageWide XL print speeds



Full online integration

- Bi-directional communication between the printer and the high-capacity stacker enables reliable operation
- Monitor high-capacity stacker status from the printer or the HP SmartStream software; the job queue halts when the high-capacity stacker has stopped

High speed

- The HP PageWide XL High-capacity Stacker is designed to maximize the speed of HP PageWide XL printers

Versatility

- Stack pages up to 40 x 48 in (102 x 122 cm) and materials from 19 to 53 lb (70 to 200 g/m²) weight
- Enable reliable handling of stiff media thanks to the stacker roof

For more information, please visit
hp.com/go/pagewidexlsolutions

Technical specifications

General	Capacity	Up to 500 pages
	Maximum page size	40 x 48 in (102 x 122 cm)
	Media weight	19 to 53 lb (70 to 200 g/m ²)
Paper handling	Sheet stacking	Face up
	Maximum stacker speed	30 A1/D per min (landscape)
	Minimum stacking speed	The minimum speed supported by the printer
	Maximum sheet size supported on the stacker table	40-inch-wide sheets (E size portrait)
	Minimum sheet size supported	A4 landscape
	Paper set supported	Full paper set supported by the printer, with 3-inch roll core
Connectivity	Power provided by printer through communication cable	
Dimensions	Dimensions with packaging	59 x 47.2 x 32 in (1500 x 1200 x 815 mm)
	Dimensions without packaging	55.1 x 43.3 in (1400 x 1100 mm) height adjustable according to printer version
Weight	Weight with packaging	352 lb (160 kg)
	Weight without packaging	235 lb (107 kg)
Environmental	Operating temperature	41 to 104°F (5 to 40°C)
	Recommended temperature	59 to 95°F (15 to 35°C)
	Operating humidity	20 to 80% RH, depending on media type
Acoustic	Sound pressure	56 dB(A) (working at 6 ips) 65 dB(A) (working at 15 ips)
	Sound power (printing)	7.1 B(A) (working at 6 ips) 8.1 B(A) (working at 15 ips)

Power	Consumption	36.57 W (maximum normal load) 8.30 W (only motors working)
	Voltage range	32Vdc, 5 A
Certification	Safety	IEC 60950-1:2005 (2nd Edition) +A1:2009 +A2:2013 / EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013 CAN/CSA-C22.2 No. 60950-1-07 +A1:2011 +A2:2014 / ANSI/UL 60950-1:2014
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI)
	Environmental	CE marking (including RoHS, WEEE, REACH). In compliance with WW RoHS materials restriction requirements in China, Korea, India, Vietnam, Turkey, Serbia, and Ukraine
Warranty	90 days	

Ordering information

Product	85B03A	HP PageWide XL Series High-Capacity Stacker
----------------	--------	---



- 1 Roof to handle stiff media
- 2 HP PageWide XL High-capacity Stacker with a capacity of up to 500 pages
- 3 Adjustable height

For more information, please visit hp.com/go/pagewidexlsolutions

© Copyright 2016, 2021 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

