

KM-3650w Specifications

BASIC SPECIFICATIONS:

Configuration:	Wide Format MFP with Standard Network Printing and Optional Network Scanning, Standard with one 500' Paper Roll, Single Sheet Bypass, Standard 512MB RAM, 80GB HDD, Optional second Paper Roll.
Technology:	LED
Resolution:	600 x 600 dpi
Original Memory:	Standard 512MB RAM, 80GB HDD
Magnification:	Full Size, 3 Reduction, 5 Enlargement Preset Ratios, 25-400% Zoom in 0.1% steps, XY Zoom
Electrical Requirements:	120V, 60Hz, 15A
Dimensions:	58.5"W x 29.4"D x 49.4"H
Weight:	463 lbs (Standard) 479 lbs (w/ Optional Paper Roll)

OUTPUT SPEEDS:

Warm-Up Time:	Within 300 Seconds, Auto Start
First Print Out (D Size):	Within 24 Seconds
First Copy Out (D Size):	Within 40 Seconds
Pages Per Minute:	4 D Size copies/prints per minute 11.8' per minute

PAPER SUPPLY:

Standard Paper Sources:	1 Roll (Max. Capacity 500' per roll), Single Sheet Bypass,
Min/Max Roll Width:	11"/36"
Min/Max Bypass Paper Size:	8.5" x 11"/36" x 48"
Max Paper Capacity:	Dual 500' Rolls and Single Sheet Bypass
Paper Weight:	16-20 lbs
Media Type:	Bond Paper, Film, Translucent Bond, Vellum

DOCUMENT SCANNER:

Scanning Direction:	Face-up Scanning
Scanning Resolution:	600 x 600 dpi
Acceptable Originals:	Width: 8.5" to 36", Length: 11" to 472"
Capacity:	Single Sheet
Standard Drawing Sizes:	Architectural/ANSI/Metric

OUTPUT:

Output Size:	Width: 11" to 36", Length: 8.3" to 141"
Standard Drawing Sizes:	Architectural/ANSI/Metric
Output Tray Capacity:	Up to 10 E Size

COPY FUNCTIONS:

Imaging Modes:	Line, Greyscale, Line/Greyscale
Continuous Copy:	Up to 99
Additional Copy Features:	Auto Magnification, Auto Center and Paper Select, Rotate Image, Margin Shift, Border Erase, Mirror Image, Interrupt, Repeat Copy, Sort/Group, Date Stamp, Background Removal, Add Job

PAPER HANDLING OPTIONS:

2ND ROLL UNIT: RU-5

Paper Capacity:	500' Roll
Paper Weight:	16 -20 lbs.
Min/Max Roll width:	11"/36"
Media Types:	Bond Paper, Film, Translucent Bond, Vellum

CONNECTIVITY:

Standard Network Print Controller

BASIC SPECIFICATIONS:

Platform:	Linux
Controller:	Duron CPU/2.6GHz
Printer Memory:	Standard 512MB RAM, 80GB HDD (Shared)
Connectivity:	Standard 10/100 Base TX

PRINT:

File Formats:	HP-GL, HP-GL/2, HP-RTL, Calcomp 906/907, CALS-G4 (TIFF 6.0), TIFF, BMP, JPEG, DXF, DWG with AutoCAD®, PDF (Option)
Windows® OS Compatibility:	Windows® 2000/XP
Supported Protocols:	TCP/IP
Drivers:	Windows Print Driver, HDI for AutoCAD®
HDI Driver Compatibility:	AutoCad® 2000/2000i/2002/2004/2005/2006
Utilities:	Remote Web Manager, Print Client KM

OPTIONAL NETWORK SCANNING: Scan System (1)

Resolution:	100, 200, 300, 400, 600
Scan Speed:	Up to 4 D's/minute
Scan Modes:	Line, Greyscale, Line/Greyscale
File Formats:	TIFF(G3/G4), CALS-G4, JPEG, BMP, PDF
Connectivity:	Standard 10/100 Base TX
Supported Protocols:	TCP/IP
Scanning Modes:	Scan to PC/File, Scan to FTP, Web Scanning
Additional Scan Features:	Continuous Scan, Background Removal, Border Erase, Mirror Image, Simultaneous Scan & Copy
Utilities:	Remote Web Manager



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.

All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2006 Kyocera Mita America, Inc.

