





Powering Color Performance... Company-wide.





The TASKalfa 2550ci multifunctional system is the ideal solution for virtually every busy office and workgroup. It meets the full range of your day-to-day document imaging needs while providing business color technology with finishing options that can help reduce outsourcing costs.

Combining power and productivity with a lower total cost of ownership, the TASKalfa 2550ci delivers the exceptional performance your business deserves.

Harness the power of your Kyocera MFP with customized business applications.



Simplify document workflow through digital imaging, distribution, retrieval and long-time archival.



PinPoint Scan Scan from your MFP to your PC with added speed, functions and versatility.



Card Authentication Use your existing HID employee identification cards to securely unlock your MFP.



Kyocera Mobile Print Simply and conveniently print

files, web pages, and images using your smartphone or tablet



SharePoint Connector Enhance collaboration utilizing

your Kyocera MFPs and your existing Microsoft SharePoint Server.



Configuration	25/25 ppm Color Multifunctional with standard
-	network print, copy and scan. Standard
	Document Processor, Duplex and 1,100 Sheet
	Paper Capacity. Optional BW Fax, Finishing and
	Paper Handling
Pages per Minute	BW/Color: 25 ppm (Letter); 13 ppm (Legal);
	13 ppm (Ledger)
Warm Up Time	45 seconds
First Page Out	Copy: 7.9 seconds Black, 10.0 seconds Color
	Print: 9.4 seconds Black, 10.9 seconds Color
Display	8.5" Color Control Panel
Resolution / Bit Depth	600 dpi / 8 bit color depth
Memory / HDD	Standard 2 GB RAM / 160 GB HDD
Duplex	Standard Duplex
Electrical Requirements	120V, 60Hz, 12.0A
Dimensions / Weight	22.23" W x 27.52" D x 33" H / 94 lbs
Paper Supply	
Standard Paper Sources	Dual 500 Sheet Drawers; 100 Sheet
	Multipurpose Tray (MPT)
Optional Paper Sources	500 x 2 Sheet Drawer
Paper Capacity	Standard: 1,100 Sheets; Maximum: 2,100 Sheets
Paper Size	5.5" x 8.5" - 11" x 17" (Statement - Ledger)
Paper Weight	Drawers: 16 lb. Bond - 140 lb. Index (60 - 256gsm);
	MPT: 16 lb. Bond - 140 lb. Index (60 - 256gsm)
Input Materials	Plain paper, Recycled paper, Material paper
Security Specifications	
Standard	Local Authentication, Network Authentication
	(IPsec, HTTPS, LDAP over SSL, SNMPv3);
	Secure Print (IPP over SSL); Scan to e-mail
	(POP3/SMTP over SSL); Scan to FTP (FTP over
	SSL); Scan to SMB/PC/USB; SSL
Optional	Data Security Kit (E): Network Data Encryption,
	HDD Overwrite Mode, HDD Data Encryption
Printer Specifications	
Controller	PowerPC 750CL/600MHz
PDLs / Emulations	PRESCRIBE, PCL6 (PCL XL and 5e),
	KPDL3 (PS3), XPS
Fonts	93 PCL Fonts, 136 PS Fonts, 8 Vista Fonts
Windows® OS Compatibility	Windows XP/2003/Vista/2008/7
Mac OS Compatibility	OS 10.x
Novell OS Compatibility	Novel NetWare 3.x/4.x/5.x/6.x
UNIX OS Compatibility	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX(LPR)
Interfaces	Standard: 10/100/1000BaseTX; High Speed
	USB 2.0, USB Host (2);
	Optional: 10/100/1000BaseTX (for dual NIC)
Network Print and Supported Protocols	TCP/IP, IPX/SPX, AppleTalk, NetBEUI, FTP,
	Port9100, LPR
Drivers / PPDs	KX Driver, Mini Driver, PPD for Mac,
	PPD for Linux/UNIX
Utilities	Kyocera Business Applications, Kyocera Net
	Admin, Kyocera Net Viewer, PDF Direct Print,

Status Monitor

ional with standard	S
an. Standard	So
x and 1,100 Sheet / Fax, Finishing and	So
13 ppm (Legal);	Fi Co So
0.0 seconds Color	
1.9 seconds Color	So
iB HDD	
H / 94 lbs	Co Ac Jo
117 04 100	00
00 Sheet	M
0.400.011	D
mum: 2,100 Sheets atement - Ledger) Index (60 - 256gsm); dex (60 - 256gsm)	E Co Tr
r, Material paper	Fa No
ork Authentication SSL, SNMPv3);	Fa
; Scan to e-mail n to FTP (FTP over l; SSL	Ty
c Data Encryption, Data Encryption	Oi Ad
and 5e),	St
s, 8 Vista Fonts 108/7	Pa Pa
6.x NX; HP-UX(LPR) eeTX; High Speed	Ed
eTX (for dual NIC) NetBEUI, FTP,	-
for Mac,	

Scan	Specific	ations

oodii opcomodiions		
Scan Type	Color and B&W Scanner	
Scan Speed	300 dpi: 48 ipm (BW/Color);	
	600 dpi: 25 ipm (BW/Color)	
Scan Resolutions	600 dpi, 400 dpi, 300 dpi, 200 dpi,	
	$200 \times 100 \text{ dpi}, 200 \text{ x } 400 \text{ dpi}$	
File Formats	TIFF, JPEG, XPS, PDF(1.4, /A)	
Connectivity / Supported Protocols	10/100/1000BaseTX, TCP/IP	
Scanning Functions	Scan to e-Mail, Scan to Folder (SMB),	
	Scan to FTP, Scan to USB	
Scanning Features	Duplex Scan, Continuous Scan	
Copy Specifications		
Image Mode	Text, Photo, Text/Photo, Auto, Manual,	
	Printed Document, Map	
Continuous Copy	1-999 / Auto Reset to 1	
Additional Features	Auto Magnification, Auto Paper Select	
Job Management	1,000 Department Codes; 100 User	
	Authentication (20 Customizable User Logins)	
Magnification / Zoom	Full Size, 5 Reduction, 5 Enlargement Preset	
	Rations, 25-400% Zoom in 1% Increments	
Document Box	Supports USB Memory for Print/Scan;	
	Private print	
Fax Specifications	Optional Fax System (W)	
Compatibility	ITU-T Group 3	
Transmission Speed / Modem	Less than 3 seconds per page / 33.6 Kbps	
Fax Transmission Selection	Normal/Fine/Ultra Fine/ Super Fine	
Network Fax Reception	Supports SMB Reception	
Fax Functions	Duplex Transmission/Reception, Dual Access,	
	100 One Touch, 50 Groups, Broadcast, Fax Reports	
Document Processor	DP-790	
Type / Capacity	Standard Reversing Document Processor	
	(RADF)/ 50 Sheets	
Original Scan Speed	Up to 48 opm (Letter)	
Acceptable Originals	5.5"x 8.5" - 11" x 17" (Statement - Ledger);	
	Simplex: 16 lb Bond - 90 lb Index (49 - 162gsm),	
	Duplex: 16-32 lb Bond (50 - 120gsm)	
Optional Finishing	DF-470	
Stack / Staple Capacity	Stack: 500 Sheets / Staple 50 Sheets (Letter),	
	30 Sheets (Legal/Ledger)	
Paper Size	Letter, Legal, Ledger	
Paper Weight	16 lb Bond - 140 lb Index (60 - 256gsm)	
Edge Staple Position	3 Positions	
Additional Options	AK-470 (Bridge Unit for Finisher), IB-50 Gigabit	
	NIC (Dual NIC), Card Authentication Kit (B),	
	Cabinet, Card Reader Holder (B)	













