



› PRINT › COPY › COLOR SCAN

TASKalfa 9600

BLACK & WHITE PRODUCTION
MULTIFUNCTIONAL SYSTEM

STREAMLINE, AUTOMATE, PROFIT . . . WITH PRODUCTION PRINT.



The TASKalfa 9600 takes productivity and revenue potential to a whole new level. Expertly engineered, its high productivity and reliability present an outstanding value proposition for customers in need of an affordable, space-saving black-and-white Production System. Intuitive walk-up and software-based controls combine with exceptional features, including broad media support, a high-speed embedded controller, user-replaceable supplies, and a wide range of professional in-line finishing. Offering the capability to help reduce or eliminate high-cost outsourcing, it is the ideal solution for customers seeking to streamline workflow and lower operating costs.

- › B&W Production MFP
- › Print Speed: 96 ppm

- › Print/Copy/Color Scan
- › Standard 220 Sheet Dual Scan Document Processor; Scan Speed: 220 ipm Color
- › Print Resolution: 1200 x 4800 dpi
- › Large Standard/Maximum Paper Supply: 3,300 Sheets / 12,650 Sheets
- › Broad Range Media Support: Thin, Thick, Textured, Coated, and NCR up to 350gsm
- › Versatile Media Handling: Air-Assisted LCT, Vacuum Feed LCT, and Cover Interposer
- › Advanced Finishing: 100 Sheet Stapling, Booklet Making, 2/3 Hole Punching, Multi-Folding, High Capacity Stacking, and More
- › Maximum Document Volumes up to 1,000,000 Impressions per Month

BASIC SPECIFICATIONS

Configuration: Black & White Production Multifunction System – Print / Copy / Color Scan
Pages Per Minute: Letter/Legal: 96 ppm
Warm Up Time: 360 Seconds or Less (Power On)
First Page Out: Copy/Print: 6.3 Seconds or Less
Display: 10.4" Color TSI
Resolution: 1200 x 4800 dpi
Memory / Hard Disk Drive: 2 GB RAM / 640 GB (320 GB x 2) HDD Standard
Duplex: Standard Duplex / Inverter Output Supports Statement to 13" x 19.2" (Custom Paper Size), 14 lb Bond – 110 lb Cover (52.3 – 300gsm)
Electrical Requirements: 208-240V, 50/60Hz, 20A (dedicated)
Typical Electricity Consumption (TEC): 11.9 kWh/week
Dimensions: 45" W x 35.4" D x 45.1" H
Weight: 937 lbs
Maximum Monthly Volume: 1,000,000 Pages per Month
Duty Cycle: 2,100,000 Pages

PAPER SUPPLY

Standard Paper Sources: Dual 1,100 Sheet Tandem Tray (Tray 1), Two - 550 Sheet Trays (Trays 2 & 3)
Paper Size Tray 1: 8.5" x 11"
Paper Size Trays 2 & 3: 5.5" x 8.5" – 12" x 18"
Paper Weight Trays 1-3: 14 lb Bond - 95 lb Cover (52 – 256 gsm)
Paper Capacity: Standard: 3,300 Sheets; Maximum: 12,650 Sheets
Input Media Types: Plain, Recycled, Colored, Letterhead, Preprinted, Prepunched, Bond, Card, OHP, Tab, Label, Gloss, Matte, Envelope, and NCR

OPTIONAL PAPER SOURCES

TK5010¹ Ledger Tray Unit
Paper Capacity: 1,000 Sheets
Paper Size: Up to 11" x 17"
Dimensions: 19.5" W x 20.9" D x 6.9" H
Weight: 22 lbs
BY5010 Multipurpose Tray
Paper Capacity: 550 Sheets
Paper Size: 5.5" x 8.5" – 13" x 19.2"
Paper Weight: 14 lb Bond – 80 lb Cover (52 – 216gsm)
Dimensions: 27.2" W x 22.1" D x 8.3" H
Weight: 44 lbs
Multipurpose Oversized Media Tray²
Paper Capacity: 500 Sheets
Paper Size: 5.5" x 8.5" – 13" x 19.2"
Custom Size: 3.94" x 5.5" – 13" x 27.5"
Paper Weight: 14 lb Bond – 80 lb Cover (52 – 216gsm)
Dimensions: 42.9" W x 22.1" D x 8.3" H when attached to the BY5010 Multipurpose Tray
Weight: 20.9 lbs
RT5070³ Letter Large Capacity Tray (LCT)
Paper Capacity: 5,000 Sheets (Trays 4 & 5: 1,100 Sheets; Tray 6: 2,800 Sheets)
Paper Size: 5.5" x 8.5" – 8.5" x 11"
Paper Weights Trays 4 & 5: 14 lb Bond – 80 lb Cover (52 – 216gsm)
Paper Weights Tray 6: 14 lb Bond – 60 lb Cover (52 – 163gsm)
Dimensions: 21.3" W x 28.7" D x 39.4" H
Weight: 233.2 lbs

RT5080⁴ Ledger Large Capacity Tray (LCT)
Paper Capacity: 4,400 Sheets (Trays 4 & 6 or 6 & 8: 1,100 Sheets; Tray 5 or 7: 2,200 Sheets)
Paper Size: 5.5" x 8.5" – 13" x 19.2"
Paper Weight Trays 4-6 or 6-8: 11 lb Bond – 110 lb Cover (40 – 300gsm)
Dimensions: 34" W x 28.7" D x 39.4" H
Weight: 407 lbs

RT5100⁵ Vacuum Feed Large Capacity Tray (LCT)
Paper Capacity: 4,400 Sheets (Trays 4 & 5 and/or 6 & 7: 2,200 Sheets)
Paper Size: 5.5" x 8.5" – 13" x 19.2"
Paper Weight Trays 4 & 5 and/or 6 & 7: 11 lb Bond – 130 lb Cover (40 – 350gsm)
Power Requirement: 100-127V
Power Consumption: Less than 860W
Dimensions: 41.5" W x 28.7" D x 39.4" H
Weight: Less than 484 lbs

BU5010⁶ Bridge Unit for RT5100 Vacuum Feed LCT
Paper Size Width: 3.94" - 13"
Paper Size Length: 5.5" x 19.2"
Paper Weight: 11 lb Bond – 130 lb Cover (40 – 350gsm)
Power Source: From LCT RT5100
Dimensions: 13" W x 28.7" D x 39.4" H
Weight: Less than 132 lbs

SECURITY SPECIFICATIONS

Security Features: Data Encryption (Address Book, Authentication Password, SSL Communication, S/MIME, IPsec Communication, HDD), User Authentication (Windows®, LDAP, Basic, User Code, 802.1x Wired), Network Protocol On/Off, Mask Type for Data Security, Data Security Unit Option, IP Filtering, Unauthorized Copy/Print Control, Quota Setting, SMTP over SSL, Mandatory Security Information Print (Compulsory Security Stamp)

UTILITIES

XG-SD, Gloria-P, Gloria-A, Gloria-AP, Gloria-FS, Maple, Karachi, RIS, Forest, UZ-D1, Basil, UZ-A1, Lime, Birdie-D, Birdie-S, Ibis, MDS Tool V1.0, Mebius, eDC-11, Client Activator, Endpoint, Green Calculator, UZ-S1, Camelot, Info Print Manager

PRINT SPECIFICATIONS

Standard Controller: Intel® Celeron® Processor P4505 / 1.86 GHz
PDLs / Emulations: Standard: PCL6, PCL5e, PDF; Optional: Adobe PostScript 3, Genuine IPDS
Print Resolution: Up to 1200 x 4800 dpi
Fonts: Standard: PCL: 45 fonts, 13 International fonts; Optional: PS3: 136 fonts; IPDS: 108 fonts
OS Compatibility: Windows: Vista/7/8/8.1/10/Server, 2008/2008 R2/2012/2012 R2; Unix: Sun Solaris, HP-UX, SCO Open Server; RedHat Linux; IBM AIX; Citrix Presentation Server 4.5/Citrix XenApp 5.0; Mac OS X v.10.2 or later; SAP R/3; NDPS Gateway; IBM iSeries/AS/400-using OS/400 Host Print Transform
Interfaces: Ethernet (100BASE-T/100BASE-TX/10BASE-TX); Type A: USB 2.0 x 3; Type B: SD Slot
Optional: IEEE1284/ECP
Network Print and Supported Protocols: Standard: TCP/IP (IPv4, IPv6); IPX/SPX
Drivers: Standard: PCL5e, PCL6 (XL), PDF, XPS, RGPL/GL2, PCL6 (XL) Universal Driver; Optional: Adobe PS3, Adobe PS3 Universal Driver, IPDS

COPY SPECIFICATIONS

Copy Resolution: Up to 1200 x 4800 dpi
Copy Features: Duplex, Simplified Display, Auto Paper Selection, Auto Reduce/Enlarge, Auto Start, Auto Tray Switching, Auto Image Density, User Codes (1,000), Job Programs (25), Electronic Sort/Stack, Image Rotation, Interrupt Copy, User Tools, Job Presets, Book/Series/Combine Copying, Cover/Chapter/Slip Sheet, Tabs, Sample Copy, Stamps/Numbering, Bates Numbering, Shift/Erase/Margin Adjustment, Customizable Home Screen, Import/Export of Preference Settings, Eco-Friendly Indicator, Power On/Off Timer, Energy Saver, Weekly Timer, External USB Keyboard Support, MFP Browser for Web Image Monitor, Copy Reservation (8), A3/DLT Counter, Mixed Originals/Batch Mode

SCAN SPECIFICATIONS

Scan Type: Color and Black & White Scanner
Scan Resolution: Up to 600 dpi (TWAIN: 1200 dpi)
File Formats: Single Page: TIFF/JPEG/PDF/High Compression PDF; Multi-Page: TIFF/PDF/High Compression PDF
Scan Speeds (B&W/color @200/300 dpi): Simplex: 120 ipm B&W / Color
Duplex: 220 ipm B&W / Color
Connectivity / Supported Protocols: Ethernet (100BASE-T/100BASE-TX/10BASE-TX); Type A: USB 2.0; Type B: SD Card Slot
Scanning Functions: Scan to USB/SD, WS Scanner, Scan-to Email/Folder/SMB/FTP/URL/NCP/PDF/A/Digitally Signed PDF/Searchable PDF, TWAIN Scanning, Scanned File Naming, LDAP Support, Universal Send, Distributed Scan Management, Preview Before Transmission, PDF Encryption, Drop Out Color Send, B&W/FC Photo, B&W/FC Text, Auto Color Selection, Auto Density, Auto Size Detection, Image Rotation, Mixed Size/SADF/Batch Mode, Reduce and Enlarge, Split Scan, JBIG2 Compression Support
Original Size: Through DP & On Glass: Up to 11" x 17"

DOCUMENT SERVER SPECIFICATIONS

Maximum Stored Documents: 15,000
Maximum Pages per Document: 1,000
Maximum Stored Pages: 15,000
Folder Management: With password, up to 200 personal folders

STANDARD DOCUMENT PROCESSOR

Type / Capacity: Dual Scan Document Processor (DSDP) / 220 Sheets
Acceptable Originals: Up to 11" x 17"

OPTIONAL 3,000 SHEET STAPLE FINISHER SR5050

Stack Capacity (Proof Tray): 250 Sheets (8.5" x 11" or smaller); 50 Sheets (8.5" x 14" or larger)
Stack Capacity (Shift Tray): 3,000 Sheets (8.5" x 11"); 1,500 Sheets (8.5" x 14" – 11" x 17"); 1,000 Sheets (12" x 18" – 13" x 19.2")
Paper Size: 5.5" x 8.5" – 13" x 19.2"
Paper Weight Proof Tray: 14 lb Bond – 80 lb Cover (52 – 216gsm)
Paper Weight Shift Tray: 11 lb Bond – 130 lb Cover (40 – 350gsm)
Output Jogger: Standard
Staple Capacity: 2 - 100 Sheets (8.5" x 11"); 2 - 50 Sheets (8.5" x 14" – 11" x 17")
Staple Position: Top, Bottom, 2 Staples, Top Slant
Optional Punch: 2 or 3 Holes, Supports 8.5" x 11" – 12" x 18"; 14 lb Bond – 80 lb Cover (52 – 216gsm)
Dimensions: 39.2" W x 28.7" D x 44.3" H
Weight: 246 lbs

OPTIONAL 2,500 SHEET BOOKLET FINISHER SR5060

Stack Capacity (Proof Tray): 250 Sheets (8.5" x 11" or smaller); 50 Sheets (8.5" x 14" or larger)
Stack Capacity (Shift Tray): 2,500 Sheets (8.5" x 11"); 1,500 Sheets (8.5" x 14" – 11" x 17"); 1,000 Sheets (12" x 18" – 13" x 19.2")
Paper Size Proof Tray: 5.5" x 8.5" – 13" x 19.2"
Paper Size Shift Tray: 5.5" x 5.5" – 13" x 19.2"

Paper Weight Proof Tray: 14 lb Bond – 80 lb Cover (52 – 216gsm)
Paper Weight Shift Tray: 11 lb Bond – 130 lb Cover (40 – 350gsm)
Output Jogger: Standard
Staple Capacity: 2 - 100 Sheets (8.5" x 11"); 2 - 50 Sheets (8.5" x 14" – 11" x 17")
Staple Position: Top, Bottom, 2 Staples, Top Slant
Saddle-Stitch Staple Capacity: 20 Sheets (8.5" x 11" – 13" x 19.2")
Saddle-Stitch Staple Position: Center 2 Position
Optional Punch: 2 or 3 Holes, Supports 8.5" x 11" – 12" x 18"; 14 lb Bond – 80 lb Cover (52 – 216gsm)
Dimensions: 39.2" W x 28.7" D x 44.3" H
Weight: 246 lbs

OPTIONAL BOOKLET TRIMMER TR5040

Trimming Type: One Side Edge
Trimming Capacity: 1 - 20 Sheets (2 - 40 pages after folding)
Paper Size: Up to 13" x 19.2"
Stack Capacity: Up to 60 Sets
Limitless Stack: Yes
Dimensions: 43.9" W x 23.3" D x 21.8" H
Weight: 165 lbs

OPTIONAL HIGH CAPACITY STACKER SK5030⁷

Paper Capacity: 5,000 Sheets; Proof Tray: 250 Sheets
Output Jogger: Standard
Rollaway Cart: Standard (Optional additional carts available)
Power Consumption: Less than 120 W
Power Supply: 120-127V, 50/60Hz, 2A
Dimensions: 35.4" W x 28.7" D x 39.8" H
Weight (Stacker): 264 lbs
Weight (Roll Away Cart): 33 lbs

ADDITIONAL ACCESSORIES

2 Source Cover Interposer CI5030
Paper Size: 5.5" x 8.5" – 13" x 19.2"
Paper Weight: 17 lb Bond – 80 lb Cover (64 – 216gsm)
Stack Capacity: 200 Sheets x 2 Trays
Dimensions: 21.2" W x 28.7" D x 50.8" H
Weight: 99 lbs
Multi-Folding Unit FD5020
Folding Type (Single Sheet Mode): Z-Fold, Half-Fold/Print Inside, Half-Fold/Print Outside, Letter Fold-In/Print Inside, Letter Fold-In/Print Outside, Letter Fold-Out, Double Parallel/Print Inside, Double Parallel/Print Outside, Gate-Fold/Print Inside, Gate-Fold/Print Outside
Folding Type (Multiple Sheets Mode): Half-Fold/Print Inside, Half-Fold/Print Outside, Letter Fold-In/Print Inside, Letter Fold-In/Print Outside, Letter Fold-Out
Paper Size (Single Sheet Mode): 8.5" x 11" – 12" x 18" (Z-Fold); 8.5" x 11" – 13" x 19.2" (Half-Fold); 8.5" x 11" (Letter-Fold)
Paper Size (Multiple Sheets Mode): 8.5" x 11" – 12" x 18" (Double Parallel Fold); 8.5" x 11" – 12" x 18" (Gate-Fold); 8.5" x 11" – 13" x 19.2" (Half-Fold); 8.5" x 11" (Letter Fold-In & Letter Fold-Out)
Dimensions: 18.5" W x 28.7" D x 39.4" H
Weight: 203 lbs

Decurl Unit DU5050

Decurl Function: Three steps pressure adjustment (from operation panel)
Paper Weight: 11 lb Bond – 130 lb Cover (40 – 350gsm)
Dimensions: 2.8" W x 20" D x 7.1" H
Weight: 11 lbs

EFI Fiery EB-34 Controller

EFI Platform: FS200 Pro
Configuration: External
Memory: 4 GB
CPU: Intel Processor G850 2.9 GHz
Host Interface Ethernet: 1000/100/10Base-T x 2
Hard Disk Drive: 500 GB
Operating System: Windows 8.1 Professional For Embedded Systems x64
Network Protocol: TCP/IP (IPv4, IPv6), SMB
Printer Description Language: Adobe PS3, PCL5e, PCL6
Maximum Resolution: 1200 dpi
Fonts: Adobe PS3 138, PCL 81
Standard Operation Panel Utilities Via TSI on MFP: EFI Driver, Command Workstation, Webtools, Hot Folders
Optional Operation Panel Utilities Via TSI on MFP: Fiery SeeQuence Impose, Fiery SeeQuence Compose, Image Viewer for Black & White, EFI Spectrophotometer (ES-2000), FACI Furniture, External Secure HDD Kit

¹ Replaces Standard Dual 1,100 Sheet Tandem Tray 1.

² Cannot be added with an RT5070.

³ If an RT5070 is selected, it can be the only Optional Paper Source added, and only one can be added.

⁴ Only one RT5080 can be selected, but it can run in tandem with one RT5100.

⁵ Up to two RT5100s can be selected. One can be selected alone, one can be added with an RT5080, or two can be selected.

⁶ A BU5010 is required if either an RT5080 and RT5100 are selected or if two RT5100s are selected.

⁷ The DU5050 is required. Up to two can be selected, and either an SR5050 or SR5060 can be added. If FD5020 is selected, then only one SK5030 can be added.

Specifications and design are subject to change without notice.
 For the latest on connectivity, visit usa.kyoceradocumentsolutions.com.
 TASKalfa is a trademark of the KYOCERA Companies. Mac OS is a trademark of Apple, Inc. Windows is a trademark of Microsoft Corporation.
 Intel and Celeron are trademarks of Intel Corporation.
 All other trademarks are the property of their respective owners.



KYOCERA Document Solutions America, Inc.
 Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA
 ©2018 KYOCERA Document Solutions America, Inc.
 IC# 855D400683