

Multifunction B&W

SAVIN IM 350F IM 430F IM 430Fb

🗹 Copier 🗹 Printer 🗹 Facsimile 🗹 Scanner



Smart office assistant

Harnessing the power of the cloud, these smart multifunction printers automate everyday document processes, leaving you free to focus on your core business activities.

Intelligent workflow tools:

- Intuitive user interface
- Savin Smart apps
- Cloud-share services
- Smartphone connection

Savin's super-sized 10.1 inch Smart Operation Panel is host to a suite of intelligent workflow tools. Pre-installed Smart apps, such as ID Card Copy, automate time-consuming processes. More applications can be installed on demand. It is easy to print from and scan to smartphones and tablets, and critical documents can be scanned in color directly to DropBox[™] or Sharepoint[™].

Simply more productive:

- 37 & 45 ppm print speeds (letter)
- 14 68 lb. Bond (52 256 gsm)
- Large paper capacity
- Offline stapler option



To save time, double-sided originals are scanned in a single pass. The first immaculate 1200 dpi print is ready in under 6 seconds. Multipage documents are produced at speeds of 37 or 45 pages per minute and can be quickly collated using the Offline Stapler option. The optional High Capacity Paper Trays further enhance productivity. It is easy to print onto envelopes and labels. And, with the printer switching from one tray to another, you need never run out of paper. Despite their advanced functionality, Savin's new multifunction printers are surprisingly easy to set up and support. With their compact design and quiet operation, they are a perfect fit for every office. Savin's installation wizard simplifies setup. To safeguard information, they support tap and go authentication and confidential documents can be securely locked, pending release. Clever energy saving features reduce power consumption and contribute to a low total cost of ownership.

A friendly and affordable solution:

- Space saving design
- Secure authentication
- Confidential printing



SAVIN IM 350F/IM 430F/IM 430Fb

	SAVIN IM 350F	SAVIN IM 430F	SAVIN IM 430Fb	
GENERAL				
Warm-up time	24 seconds			
First output speed: B/W	Less than 6.0 seconds	Less than 5.0 seconds	Less than 5.0 seconds	
Continuous output speed	37 ppm	45 ppm	45 ppm	
	2 GB	45 ppm	45 ppm	
Memory: standard	2 GB			
Memory: maximum				
HDD: standard	320 GB			
HDD: maximum	320 GB			
SPDF capacity	50 sheets			
Weight	67.24 lbs. (30.5 kg)			
Dimensions: W x D x H	18.7" x 17.4" x 20.1" (476 x 442 x 510mm)			
Power source	120-127V/12A 60Hz			
COPIER (STANDARD)				
Multiple copying	Up to 999 copies			
Copy resolution: maximum	600 x 600 dpi			
Zoom	From 25% to 400% in 1% steps			
PRINTER (STANDARD)				
CPU	Intel Atom Processor Bay Trail 1.46GHz			
Printer language: standard	PCL5e, PCL6, PostScript 3 (emulation), PDF direct (emulation)			
Printer language: option	Genuine Adobe® PostScript® 3™, IPDS, PDF Direct from Adobe®			
Print resolution: maximum	Genuine Adobe" PostScript" 3", IPDS, PDF Direct from Adobe" 1,200 x 1,200 dpi			
Network interface: standard	1,200 x 1,200 dpi Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host 2.0			
Network interface: option	Ethernet 10 base-1/100 base-1/100 base-1/000 base-1/008 Host 2:0 Wireless LAN (IEEE 802.11a/b/g/n), Additional NIC (2nd port), Extended USB Board, File Format Converter			
Mobile printing capability	Apple AirPrint™, Mopria, Google Cloud Print, NFC, Ricoh Smart Device Connector			
Network protocol	TCP/IP (IP v4, IP v6)			
Windows [®] environments	Windows [®] 7, Windows [®] 8.1, Windows [®] 10, Windows [®] Serve	2008, Windows [®] Server 2008R2, Windows [®] Server 2012	, Windows [®] Server 2012R2, Windows [®] Server 2016	
Mac OS environments	Macintosh OS X v10.10 or later			
UNIX environments	UNIX Sun® SolarisUNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM® AIX, Citrix XenApp			
SAP [®] environments	SAP [®] R/3 [®] , SAP [®] S/4 [®]			
Other supported environments	NDPS Gateway, AS/400 [®] using OS/400 Host Print Transform, II	BM iSeries		
SCANNER (STANDARD)				
Scanning: B/W	45.7 ipm			
Scanning: full color	45.7 ipm			
Resolution: maximum	600 dpi			
Compression method	TIFF (MH, MR, MMR, JBIG2), Grayscale			
File formats	Single Page TIFF, Single page JPEG, Single page PDF, Single page Multi page PDF/A	e High compression PDF, Single page PDF/A, Multi page TI	FF, Multi page PDF, Multi page High compression PDF,	
Scan modes	E-mail, Folder, USB, SD Card			
FAX (STANDARD)				
Circuit	PSTN, PBX			
Transmission speed	2 seconds (200x100 dpi, JBIG, ITUT #1 chart TTI off, memory t	ransmission)		
Modem speed: maximum	33.6 Kbps			
Resolution: standard	8x7.7 line per mm, 200x200 dpi			
Compression method	MH, MR, MMR, JBIG			
Scanning speed	28 spm			
Memory: standard	4 MB (Approx. 320 pages)			
Memory: maximum	4 MB (Approx. 320 pages)			
PAPER HANDLING				
Recommended paper size	Standard paper tray(s): 5.5″ x 8.5″ - 8.5″ x 14″ (A6-A4, B6-B5) Optional paper tray(s): 5.5″ x 8.5″ - 8.5″ x 14″ (A6-A4, B6-B5) Bypass tray: 5.5″ x 8.5″ - 8.5″ x 14″ (A6-A4, B6-B5) Custom Sizes - Width: 2.36″ - 8.5″ (60 - 216 mm), Length: 5.0″ - 35.43″ (127 - 900 mm)			
Paper input: standard	500 sheets			
Paper input: maximum	2,100 sheets			
Paper output: standard	250 sheets			
Paper weight	Trays: 14 - 58 lb. Bond (52 - 220 g/m²) Bypass: 14 - 68 lb. Bond (52 - 256 g/m²) Duplex: 14 - 43 lb. Bond (52 - 162 g/m²)			
	spread of the second se			
Paper types	Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-p	inted, Bond, Coated, Envelope, Label, OHP		

SAVIN IM 350F/IM 430F/IM 430Fb

	SAVIN IM 350F	SAVIN IM 430F	SAVIN IM 430Fb	
ECOLOGY				
Power consumption: Maximum (kW)	Less than 1,380 W			
Power consumption: operation	566 W	628 W	628 W	
Power consumption: ready	91 W			
Power consumption: sleep	0.7 W	0.74 W	0.74 W	
TEC	1.5 kWh	1.9 kWh	1.9 kWh	
ENERGY STAR®	Certified			
EPEAT®	Gold Rated*			
	* EPEAT Gold rating is applicable only in the USA.			
OUTPUT TRAYS				
1 x 250-sheet Paper Tray (PB 1110)	Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6); Paper weight: 14-58 lb. Bond (52-220 g/m²)			
1 x 500-sheet Paper Tray (PB 1120)	Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6-B5); Paper weight: 14-58 lb. Bond (52-220 g/m ²)			

OTHER OPTIONS

IPDS Unit Type M34*, Offline Stapler Type M34, PostScript 3 Unit Type M34, IEEE 802.11 Interface Unit Type M24, USB Device Server Option Type M19A, File Format Converter Type M19, OCR Unit Type M13, Page Keeper Type M28, Extended USB Board Type M19, Medium Cabinet Type P, Tall Cabinet Type Q, Caster Table Type M34, Optional Counter Interface Unit Type M12, NFC Card Reader Type M27

* Available late 2019.

CONSUMABLE

	Starter Supplies	Yield (CTN)
SAVIN IM 350F		
Print Cartridge IM 350	14,000	14,000
Refill Staple Type M34		5,000
SAVIN IM 430F		
Print Cartridge IM 430	17,400	17,400
Refill Staple Type M34		5,000
SAVIN IM 430Fb		
Print Cartridge P 501H		14,000
Print Cartridge P 501L	6,000	3,000
Refill Staple Type M34		5,000
Drum Unit P 501		40,000
Maintenance Kit P 501		120,000

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Savin parts and supplies.

Some features may require additional options and/or charges.

Ricoh USA, Inc.

For further information contact us at:

70 Valley Stream Parkway Malvern, PA 19355







Ricoh USA, Inc., 70 Valley Stream Parkway, Malvern, PA 19355, 1-877-472-8460 ©2019 Ricoh USA, Inc. All rights reserved. Savin® and the Savin logo are registered trademarks of Ricoh USA, Inc. Ricoh® and the Ricoh Logo are registered trademarks of Ricoh Company Ltd. All other trademarks are the property of their respective owners. Savin products and services are offered by Ricoh USA, Inc. and its affiliates. The content of this document, and the appearance, features and specifications of Savin products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Savin products and services are as set forth in the overcent. in the express warranty statements accompanying them