

# TOSHIBA

## **e-STUDIO5525AC/6525AC**

- High-Speed – Up to 55 & 65PPM
- High-Volume
- Advanced Security Features
- Solutions Ready
- Environmentally Friendly



## MAIN SPECIFICATIONS

<b>Copy System</b>	Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing
<b>Display</b>	10.1" Color WSVGA Touch Screen Tilting Display
<b>Copy Speed</b>	55/65 PPM (LT)
<b>First Copy Out</b>	Color: Less Than 5.7/5.7 Seconds Monochrome: Less Than 4.3/4.3 Seconds
<b>Warm-Up Time</b>	From powering on: Approx. 26 Seconds From Sleep & Low Power: Less Than 20 Seconds
<b>Copy Resolution</b>	600 x 600 dpi
<b>Stack Feed Bypass</b>	3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope
<b>Multiple Copying</b>	Up to 999 Copies
<b>Paper Capacity</b>	Standard 1,200 Sheets/Max. 5,200 Sheets
<b>Original Feed</b>	300-Sheet DSD/ or DSD/ with Double Feed Detection or 100-Sheet RADF
<b>Scan Speed &amp; Weights</b>	DSD/ Scan: 70IPM (Monochrome or Color), Simplex or Duplex: 9.3-110lb Bond, RADF Scan: 50IPM (Monochrome or Color), Simplex: 9.3-41.8lb Bond, Duplex: 13.3-41.8lb Bond
<b>Max. Original Size</b>	LD/A3
<b>Paper Feed Sizes</b>	Drawer 1: 550 Sheets-ST-R to LD Drawer 2: 550 Sheets-ST-R to 12.5" x 18" Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to 12.5" x 18", 12" x 47" Banner Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12.5" x 18" Opt. 550-Sheet Drawer for PFP-ST-R to 12.5" x 18" Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Opt. 2,000-Sheet External LCF-LT Only Standard: 550 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 100 Sheets-14lb Bond-110lb Cover Opt. 550-Sheet Paper Feed Pedestal-16lb Bond-110lb Cover Opt. 550 Sheets Drawer for PFP-16lb Bond-110lb Cover Opt. Envelope Cassette for PFP-16lb Bond-140lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-17 lb-28lb Bond Opt. 2,000-Sheet External LCF-LT 16lb Bond-110lb Cover Standard Automatic Duplex Unit (16lb Bond-140lb Index)
<b>Paper Weights</b>	25% to 400% Max. 106K/115K Month (Color: 100%) Max. 212K/230K Month (Monochrome: 100%) Approx.173lb 23" (W) x 25.2" (D) x 31" (H) CMY: 38K, K: 39.8K @ 5% 120 Volts, 50/60 Hz, 12 Amperes Maximum 1.8kW (120V) e-STUDIO5525AC: NEMA 5-15, e-STUDIO6525AC: NEMA 5-20 6GB 128GB Solid State Drive (SSD)
<b>Duplex</b>	
<b>Reproduction Ratio</b>	
<b>Max Duty Cycle</b>	
<b>Weight</b>	
<b>Approx. Dimensions</b>	
<b>CMYK Toner Yield</b>	
<b>Power Source</b>	
<b>Power Consumption</b>	
<b>Plug Type</b>	
<b>Memory</b>	
<b>Hard Disk Drive</b>	

## e-BRIDGE NEXT PRINT SPECIFICATIONS

<b>PDL</b>	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
<b>Print Resolution</b>	600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (Color/2 bit) or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
<b>Operating Systems</b>	Windows® 8.1,10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux® TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
<b>Network Protocols</b>	SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP
<b>Printing Protocols</b>	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12
<b>Print Drivers</b>	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
<b>Interface</b>	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
<b>Wireless Device</b>	TopAccess
<b>Device Management</b>	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
<b>Account Control</b>	
<b>Accessibility Features</b>	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist



Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

## Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)\* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication \*Conformance with HCD-PPv1.0 in High Security Mode ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65 WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

## Environmental Standards Certifications

## SCAN SPECIFICATIONS

<b>Scan Speed</b>	DSD/ Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) RADF Scan: Up to 73 IPM (Monochrome or Color) Standard: Full Color, Auto Color, Monochrome, Grayscale DOC/XLS/PPT/PDF
<b>Scan Modes</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>OCR</b>	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.), Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
<b>Scan Resolution</b>	Color/Grayscale: JPEG (High, Middle, Low)
<b>File Formats</b>	
<b>Image Compression</b>	

## FACSIMILE SPECIFICATIONS

<b>Compatibility</b>	Super G3
<b>Data Compression</b>	MH/MR/MMR/JBIG
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Memory Transmission</b>	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
<b>Scan Speed</b>	0.7 Seconds Per Page, Maximum 73 IPM

## e-FILING SPECIFICATIONS

<b>Operation Method</b>	Color Touch Screen Control Panel or Client PC
<b>Number of Boxes</b>	1 Public Box, 200 Private User Boxes
<b>Capacity of Boxes</b>	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

## ACCESSORIES (OPTIONS)

<b>Platen &amp; Document Feeder Options</b>		Unicode Font Enabler	GS1007NODE
DSD/	MR4010	Multi-Station Print Enabler	
DSD/ with Double Feed Detection	MR4020	Per Seat License	GS1090NODE
RADF	MR3033	e-BRIDGE Plus for OneDrive for Business V3.0	GB2300NODE
Platen Cover	KA5005PC	e-BRIDGE Plus for SharePoint Online V3.0	GB2310NODE
<b>Additional Paper Options</b>		e-BRIDGE Plus for Exchange Online V3.0	GB2320NODE
Paper Feed Pedestal	KD1072	e-BRIDGE Plus for Gmail	GB2380NODE
Drawer Module	MY1052	e-BRIDGE Plus for Google Workspace	GB2390NODE
Envelope Cassette Option	MY1053	Hardcopy Security Printing	GP1190NODE
Large Capacity Feeder	KD1073LT	Security SSD (512GB)	GE1280
External Large Capacity Feeder	MP2002	FIPS HDD (320GB)	GE1260
<b>Finishing Options</b>		e-BRIDGE Plus Voice Guidance	GB2540NODE
65-Sheet Staple Finisher	MJ1113	e-BRIDGE Global Print	GB2550NODE
65-Sheet Saddle-Stitch Finisher	MJ1114	<b>Miscellaneous Options</b>	
Hole Punch for MJ1113/MJ1114	MJ6107	Card Reader Holder	GR1320
Bridge Kit	KN5005	Accessory Tray	GR1330
Job Separator	MJ5015	Panel 10-Key Option	GR1340
<b>Connectivity/Security Options</b>		Stand	STAND5015
FAX Unit/2 <sup>nd</sup> Line for FAX Unit	GD1370N	Work Tray	KK5005
Wireless LAN/Bluetooth	GN4030A3	Manual Pocket	KK5008
Fax Over IP License Key	GS1100NODE	Harness for Coin Controller	QK1280
Bluetooth Keyboard	GR9001	Accessible Arm	KK2560
2 <sup>nd</sup> NIC Holder	GR1430		
USB Hub	GR1420		
Meta Scan Enabler	GS1010NODE		
IPSec Enabler	GP1080NODE		

## Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000  
959 Route 46 East, 5th Floor, Parsippany, NJ 07054  
Tel: 973-316-2700  
8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631  
Tel: 773-380-6000  
2037 Bakers Mill Rd., Dacula, GA 30019  
Tel: 678-546-9385  
25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000  
www.business.toshiba.com

## East Coast

## Midwest

## South

## West Coast

## Website