

**e-STUDIO™ 2010AC**  
**e-STUDIO™ 2510AC**

- > Colour Multifunction Printer
- > Up to 25 PPM
- > Small Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready



# e-STUDIO™ 2010Ac/2510Ac

## Main Specifications

<b>Copy System</b>	Indirect Electrostatic Photographic Method/OPC/LED Printing/ Heat Roller Fusing
<b>Display</b>	10.1" Colour WSVGA Touch Screen Tilting Display
<b>Copy Speed</b>	20/25 PPM (A4)
<b>First Copy Out</b>	Colour: 9.5/9.5 seconds Monochrome: 7.1/7.1 seconds
<b>Warm-Up Time</b>	Approx. 21 Seconds
<b>Copy Resolution</b>	600 x 600 dpi
<b>Stack Feed Bypass</b>	100 x 148 mm to A3, Envelope
<b>Multiple Copying</b>	Up to 999 Copies
<b>Paper Capacity</b>	Standard 350 Sheets/Max. 2,900 Sheets
<b>Original Feed</b>	Optional 100-Sheet RADF
<b>Scan Speed &amp; Weights</b>	RADF Scan: Up to 73 IPM (Monochrome or Colour), Simplex: 35-157 gsm, Duplex: 50-157 gsm
<b>Max. Original Size</b>	A3
<b>Paper Feed Sizes</b>	Drawer 1: 250 Sheets-A5-R to A3 Stack Feed Bypass: 100 Sheets- 100 x 148 mm to A3 Opt. Paper Feed Unit: 550 Sheets-A5-R to A3 Opt. 550-Sheet Paper Feed Pedestal-A5-R to A3 Opt. 550-Sheet Drawer for PFP-A5-R to A3 Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-16K-R to A4-R Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-A4 Only Standard: 250 Sheets- 60-163 gsm Stack Feed Bypass: 100 Sheets-60 -209 gsm Opt. Paper Feed Unit: 550 Sheets- 60-163 gsm Opt. 550-Sheet Paper Feed Pedestal: 60-163 gsm Opt. 550-Sheet Drawer for PFP: 60-163 gsm Opt. Envelope Cassette for PFP: 60- 163 gsm Opt. 2,000-Sheet Tandem LCF (Pedestal Type): 64-105 gsm Standard Automatic Duplex Unit: 60-163 gsm
<b>Paper Weights</b>	25% to 400% Max. 67.2K Month (e-STUDIO 2010AC) Max. 84K Month (e-STUDIO 2510AC) Approx. 57 kg 575 mm (W) x 586 mm(D) x 787 mm (H)
<b>Duplex</b>	Standard Automatic Duplex Unit: 60-163 gsm
<b>Reproduction Ratio</b>	25% to 400%
<b>Max Duty Cycle</b>	Max. 67.2K Month (e-STUDIO 2010AC) Max. 84K Month (e-STUDIO 2510AC) Approx. 57 kg
<b>Weight</b>	575 mm (W) x 586 mm(D) x 787 mm (H)
<b>Approx. Dimensions</b>	CMY: 33.6K, BK: 38.4K @ 5%
<b>CMYK Toner Yield</b>	220-240 Volts, 50/60 Hz, 12 Amps
<b>Power Source</b>	Maximum 2.0kW (220-240V)
<b>Power Consumption</b>	Intel Atom™ 1.33GHz (Dual-Core)
<b>CPU</b>	2GB, Max. 4GB
<b>Memory</b>	320GB Self-Encrypting Drive
<b>Hard Disk Drive</b>	

## e-BRIDGE Next Print Specifications

<b>PDL</b>	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
<b>Print Speed</b>	20/25 Pages Per Minute (A4)
<b>Print Resolution</b>	600 x 600 dpi (5 bit), 600 x 1,200 dpi (1 bit) PS3 Only
<b>Operating Systems</b>	Windows Server® 2008 R2, R2 SP1, 2008/SP2, Windows® 7,8,1,10, Windows Server® 2012/R2, Windows Server® 2016, Macintosh® (MacOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13), Unix®, Linux®
<b>Network Protocols</b>	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh® Environments
<b>Printing Protocols</b>	SMB, LPR/LPD, IPP (Ver.2.0) w/Authentication, AppleTalk® PAP or EtherTalk, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ IPrint, WS Print, FTP
<b>Print Drivers</b>	Windows Server® 2008 SP2 (32-bit, 64-bit) Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016, Windows® 10 (32-bit, 64-bit), MacOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13
<b>Interface</b>	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed)
<b>Wireless Device</b>	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
<b>Device Management</b>	TopAccess, EFMS 6.30 (e-BRIDGE Fleet Management Software)
<b>Account Control</b>	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
<b>Accessibility Features</b>	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts
<b>Security Features</b>	User Authentication, On-Board Data Scramble Function, SCEP, Disable



e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)\*, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for firmware update, Integrity Check function, Image Log, Card Authentication, \*Conformance with HCD-PPv1.0 in High security mode.  
ENERGY STAR® (V2.0), EPEAT Gold  
WHQL (Windows® 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell®, Citrix®, SAP, AirPrint® and Mopria®

## Environmental Stds. Certification

## Scan Specifications

<b>Scan Speed</b>	RADF Scan: Up to 73 IPM (Monochrome or Colour)
<b>Scan Modes</b>	Standard: Full Colour, Auto Colour, Monochrome, Grayscale
<b>Scan Resolution</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>File Formats</b>	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Colour/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
<b>Image Compression</b>	Colour/Grayscale: JPEG (High, Middle, Low)

## Facsimile Specifications

<b>Compatibility</b>	Super G3
<b>Data Compression</b>	MH/MR/MMR/JBIG
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Memory Transmission</b>	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
<b>Scan Speed</b>	0.7 Seconds Per Page, Maximum 73 IPM

## e-Filing Specifications

<b>Operation Method</b>	Colour Touch Screen Control Panel or Client PC
<b>Number of Boxes</b>	1 Public Box, 200 Private User Boxes
<b>Capacity of Boxes</b>	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

## Accessories (Options)

<b>Platen &amp; Document Feeder Options</b>		Unicod Font Enabler	GS-1007
RADF	MR-3031-B	Embedded OCR Enabler	
Platen Cover	KA-5005PC	Single License	GS-1080
		Five Licenses	GS-1085
<b>Additional Paper Options</b>		Multi-Station Print Enabler	
Paper Feed Pedestal	KD-1058-B	Single License	GS-1090
Paper Feed Unit	MY-1047-B	Five Licenses	GS-1095
Drawer Module	MY-1048-B	USB Hub Option	GR-1310
Envelope Cassette Option	MY-1049-B	SharePoint® Connector	GB-1440
Large Capacity Feeder	KD-1059A4-B	Exchange Connector	GB-1450
		Google Docs™ Connector	GB-1540
<b>Finishing Options</b>		External Interface Enabler	
Inner Finisher	MJ-1042-B	Data OverWrite Enabler	GP-1070
Saddle-Stitch Finisher	MJ-1110-B	Monotype Font Option	GB-2050
Hole Punch Unit (For MJ1042)	MJ-6011		
Hole Punch Unit (For MJ1110)	MJ-6105	<b>Miscellaneous Options</b>	
Bridge Kit	KN-5005	Stand	
Job Separator	MJ-5014	Accessible Arm	KK-2560
		Work Tray	KK-5005
<b>Connectivity/Security Options</b>		Manual Pocket	KK-5008
FAX Unit/2nd Line for FAX Unit	GD-1370	Harness Kit for Coin Controller	GQ-1280
Accessory Tray	GR-1330		
Panel 10-Key Option	GR-1340		
Card Reader Holder	GR-1320		
4GB Memory Option	GC-1410		
FIPS HDD	GE-1230		
Hardcopy Security Printing	GP-1190A		
Meta Scan Enabler	GS-1010		
IPsec Enabler	GP-1080		

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Productivity and paper specifications are related to paper size of A4 and a paper weight of 80 g/m<sup>2</sup> if not otherwise mentioned.

Copyright ©2018 TOSHIBA TEC.

R180511V1300-TTEC

For more information, please call or visit us at

**TOSHIBA**  
Business Machines & Equipment  
10, Taher Tower, 2nd Floor, Suite # 319~320,  
Gulshan-2, Dhaka-1212, Bangladesh  
Phone: 02, 9890665, 9886192, 01709998383~90  
Website: www.bmebd.com

TSE Version X.0