

WorkCentre® 7346 Colour Multifunction System



WorkCentre 7346

shown with High-Capacity Tandem Tray and Professional Finisher options.

WorkCentre® 7346

Output Speed – Printing and Copying	
Black and White	Up to 45 ppm A4/210 x 297 mm, Up to 27 ppm 216 x 356 mm, Up to 22 ppm A3/297 x 420 mm
Colour	Up to 40 ppm A4/210 x 297 mm, Up to 24 ppm 216 x 356 mm, Up to 20 ppm A3/297 x 420 mm

Print Specifications

System	
--------	--

Memory	1.5 GB
System Disk	Minimum 40 GB

Network Printing - Network Controller

Processor	667 MHz
Printer Languages (auto sensing/ switching)	Adobe Postscript® 3 TIFF PCL5c PDF 1.5 PCL 6 HP-GL2™ XPS®

Network Printing - Resolution

Print Engine: 1200 x 1200 dpi

Network Printing – Printing features

Print Calibration

Secure print

Delay print (specific time)

Sample set

Booklet creation

Cover selection

Paper selection by attribute

N-up

Saddle-stitch booklet making (requires Professional Finisher)

Hole Punch (requires Professional Finisher or Advanced Office Finisher)

Booklet Fold / V Folding (requires Professional Finisher)

Watermark

Fit to new paper size

Transparency Separators

Banner sheet enable/disable

Output tray selection

Image quality: High Speed ($600 \times 600 \times 1$), High Quality ($600 \times 600 \times 8$), High Resolution ($1200 \times 1200 \times 1$)

Draft mode

Store and recall driver settings

Reduce/enlarge

Mirror image

Margins

Bi-Directional

Print Protocols and Networks

Print Protocols and r	retworks		
Physical	Ethernet 100BaseT/10BaseT USB printer port (optional) Wireless Ethernet (IEEE 802.11b) v Parallel Port (optional)	ria third-party adapters	
Operating Systems	Microsoft® Windows® XP® 32-bit, X Vista 32-bit, Windows Vista 64-bit Mac OS® 10.3 and above AIX 5Iv5.3 HP UX 11.0, 11i v2 Solaris 8, 9, 10 Linux® FedoraCore 1, 5 RedHat Enterprise Linux 4 SUSE 10.x	(P 64-bit, Windows Server 2003 32-bit, Wind	lows Server 2003 64-bit, Windows
Network Protocols			Port 9100, IPv4/IPv6
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, DDN	S, SLP® v2, HTTP, RARP, DHCP Autonet, SSL	
Fonts	Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts PCL: 84 scalable fonts, line printer bitmap font		
Print Drivers	Environment	PCL5c and PCL 6	PostScript
(Vista XPS mini driver available)	Windows 2003/XP 32 Bit Windows 2003/XP 64 Bit Windows Vista/Vista 32 Bit Windows Vista/Vista 64 Bit (Microsoft certified)	Bi-directional with user-selectable interface (standard and enhanced)	Bi-directional with user-selectable interface (standard and enhanced)
	Macintosh® System OS 10.3.0 and above	N/A	Enhanced PPD file
	UNIX	N/A	Bi-directional with Xerox Custom

Graphical User Interface

Print Submission Tools	 Command prompt LPR/UNIX tool for print submission Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation) Contents Bridge tool supports TIFF/PDF/XPS and Office 2007 direct print
Device Management	
Management Support	SNMP Version 1, SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIB II RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v. 2
Xerox CentreWare Web	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
IP Filter	Allows administrator to control print access to device via IP address.
Xerox CentreWare® for Unicenter TNG®	 Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk
Xerox CentreWare® for Tivoli® Netware®	 Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by Tivoli NetView Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC)
Xerox CentreWare® for Microsoft Management Console (MMC)	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.
Xerox CentreWare® for HP® OpenView®	 Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by HP OpenView Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via colour-coded icons Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView
Xerox Device Types for SAP R/3 Environment Information available at www.xeroxofficesap solutions.com	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): • Simplex or duplex printing • Finishing – single or dual stapling • Tray pull location from any tray • Print security via PIN ID capability at the WorkCentre
Xerox SAP R/3 Intelligent Barcode Utility (Optional) Information available at www.xeroxofficesap solutions.com	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded on network controller • Tray status/contents • Consumables status
Xerox Barcode Pro PS (optional) Information available at www.xeroxofficesap solutions.com	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.

Smart eSolutions		
Meter Assistant	Device Direct or via proxy	
Centreware® internet	services — Integrated device Web Page	
Device Status	Web server embedded on network controller • Tray status/contents • Consumables status	
Print Queue Viewing	Complete job print queue management – hold, release, promote and delete	
Job Submission	Print-ready files (PS, PCL, TIFF, PDF, XPS) Output feature selection	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Windows XP: Netscape Navigator®, Firefox® Microsoft Internet Explorer Macintosh 9.x/OS X: Netscape Navigator 6.x, Mac Safari, Firefox Linux: Netscape® 6.x	
EFI Fiery System 8e®	Network Server (Optionαl)	
Processor	2.8 GHz	
Memory (ESS)	512 MB	
System Disk	80 GB minimum	
Print Languages (PDL)	PostScript 3, PCL 6 emulation	
Features	Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management, Job Preview, Merge and Properties and Manual Load Balancing Pantone Calibrated Certification Expert Colour Settings; Profile, Rendering and Simulation Variable Data – Free Form	
Optional	Hot folders Optional Virtual Printer Spot On Colour Management Auto Trapping Impose	
Scan Specifications		
Scanning (Optional)		
Capability	Colour Scanning, Greyscale, Black and White, Auto Colour	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs	
Input Speed	Scan at 50 ipm black and white/45 ipm colour (216 x 279 mm/A4 long edge feed)	
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Bit depth: 1 bit (black and white), 8 bit (greyscale), 24 bit (colour)	
Maximum Scan Area	297 x 432 mm	
Secure Access and Authentication	Optional secure device login with network user name and password Supports: Kerberos (UNIX/Windows Server 2003), SMB (Windows Server 2003/Vista) LDAP	

Network Protocol	FTP via TCP/IP Microsoft SMB via TCP/IP NetWare, HTTP and HTTPS
File Formats	TIFF 6.0 or TTN2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF with MRC, JPEG, G3 MH, G4 MMR or JBIG2 compression JPEG XPS Text Searchable PDF Encrypted PDF
Document Management Fields	One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard
Scan Feature Options	Mixed size originals Bound originals Edge erase Reduction enlargement Fit to size Scan Build Job Compression Quality/File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression
Supported Scan Destinations (Varies by scanning software options purchased.)	Scan to network server Scan to remote email destinations via direct SMTP addresses or via various network scanning software options Scan to application (Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop™ (Professional and SE editions) Scan to Windows XP client SMB or FTP Scan to Mailbox Scan to Home
Scan to PC Desktop SE	 A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools ScanSoft PaperPort (for desktop/client installation) – image viewing and file management software ScanSoft OmniPage (for desktop/client installation) – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops.
Scan to PC Desktop Professional	 A desktop and server based offering that provides document imaging, archiving, editing and organisation tools ScanSoft PaperPort Pro (for desktop/client installation) – image viewing and file management software ScanSoft OmniPage Pro (for desktop/client installation) – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an Email inbox polling capability.
Email (Included with	Scanning Option)
Capability	Colour scanning, Auto Colour, Greyscale, Black and White Direct document email from device Manual or directory Exchange/Notes/LDAP address searching
Network Protocol	SMTP, S/MIME, LDAP, LDAPs encoded
Authentication	Device login with network user name and password Supports: Kerberos (UNIX/Windows 2003 Server), SMB, (Windows 2003 Server) LDAP Domino
Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)
Scan to Mailbox (Incl	uded with the Scanning Option)
Capability	Colour, Auto Colour, Black and White
Features	Images can be scanned, printed and faxed directly to the device hard drive and stored in a mailbox. Scan and fax images that are stored in the mailbox can then be emailed, sent via fax, sent via IFax, routed to a PC, an FTP or SM site via Job Flow Sheets.

Try (CTTT) group 3 quality/resolution superfine/60x 6ox 9 super fine/40x 40x 40x 16ine/20x 20x 10x 16ine/30x 10x 16ine/30x 10x 16ine/30x 16ine/3	Thumbnail Preview (Optional)		
Network Fax Server Integration (Optional)		Images that are stored in the mailbox can be viewed at the device.	
Fax Send Features One or two-sided scanning Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi) On or two-sided printing Quantity Staple on/off Collete on/off Finisher output tray selection (top tray or main tray) Secure print on/off Fax Vendors Multiple vendors, certified by the Xerox Alliance Partners Programme For details, visit www.xerox.com Fax (Optional) – Standard/200x100 dpi ITY (CCITT) group 3 quality/resolution superfine/600x600, superfine/400 x 400, fine/200x200, standard/200x100 dpi Speed/Modem(s) V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter. Speed/Compression MH/G3, MMR/G4, JBig Super G3 Fax Send Features Fax Send Features Fax Send Features Fox from pint driver Auto fax transmission reduction Dege-by-page job status at the machine Fox from platen Delay start Automatic ower sheets Pinority send Broadcast up to 200 recipients Booklet Scan PSTN Fax Linternet Fax Lun Fax Lun Fax Lun Fax Fax Forward When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the molibox can be routed to an Enaul, an FTP or SMB location or a fax. Fax Receive Fax Receive Fox Receive Fox Pox Pox Pox Pox Pox Pox Pox Pox Pox P	Fax Specifications		
Phone number entry Add to send list (50 numbers moximum) Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi) Original type (photo and text, photo, text) Fax Print Features One or two-sided printing Quantity Staple on/off Collete on/off Finisher output tray selection (top tray or main tray) Secure print on/off Fix Vendors Multiple vendors, certified by the Xerox Alliance Partners Programme For details, visit www.xerox.com Fox (Optional) – Standard/200x100 dpi ITY (CCITT) group 3 quality/resolution superfine/600x600, superfine/400 x 400, fine/200x200, standard/200x100 dpi Speed/Modem(s) V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter. Speed/Compression MH/G3, MMR/G4, JBig Super G3 Fox Send Features Fox From print driver Auto fix transmission reduction Page-by-page job status at the machine fox from platial cover sheets Priority send Broadcast up to 200 recipients booklet Scan PSTN Fox Internet Fox LAN Fox LAN Fox When enabled with the scan and fox kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fox. Fox Receive Mailboxes Pax Receive Mailboxes	Network Fax Server Ir	ntegration (Optional)	
Speed/Modem(s) Fax Yendors Multiple vendors, certified by the Xerox Alliance Partners Programme For details, visit wow.xerox.com Fax (Optional) – Standard with One or Three line Fax option ITY (CCITT) group 3 quality/resolution superfine/600x600, superfine/400 x 400, fine/200x200, standard/200x100 dpi Speed/Modem(s) V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter. Speed/Compression MH/G3, MMR/G4, JBIg Super G3 Fax Send Features Fax from pint driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic memory resend Automatic memory resend Priority send Broadcast up to 200 recipients Booklet Scan PSTN Fox Internet Fax LAN Fax When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax. Fax Reports Activity report Dial directory Transmission confirmation Pending fax Mulboxe Mailboxe Up to 200 password-protected moilboxes	Fax Send Features	Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi)	
For details, visit www.xerox.com Fax (Optional) – Standard with One or Three line Fax option ITY (CCITT) group 3 quality/resolution superfine/600x600, superfine/400 x 400, fine/200x200, standard/200x100 dpi Speed/Modem(s) V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter. Speed/Compression MH/G3, MMR/G4, JBig Super G3 Fax Send Features Fax from pint driver Automatic for far shirts on eduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast up to 200 recipients Booklet Scan PSTN Fax Internet Fax LAN Fax One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax. Fax Reports Dial directory Transmission confirmation Pending fax Mailboxes Up to 200 password-protected mailboxes	Fax Print Features	Quantity Staple on/off Collate on/off Finisher output tray selection (top tray or main tray)	
ITY (CCITT) group 3 quality/resolution superfine/600x600, superfine/400 x 400, fine/200x200, standard/200x100 dpi Speed/Modem(s) V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter. Speed/Compression MH/G3, MMR/G4, JBig Super G3 Fax Send Features Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast up to 200 recipients Booklet Scan PSTN Fax Internet Fax LAN Fax One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention Fax Forward When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax. Fax Reports Dial directory Transmission confirmation Pending fax Mailboxes Up to 200 password-protected mailboxes	Fax Vendors		
Speed/Modem(s) V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter. Speed/Compression MH/G3, MMR/G4, JBig Super G3 Fax Send Features Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic cover sheets Priority send Broadcast up to 200 recipients Booklet Scan PSTN Fax Internet Fax LAN Fax Fax Receive Features When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax. Fax Reports Activity report Dial directory Transmission confirmation Pending fax Mailboxes Up to 200 password-protected mailboxes	Fax (Optional) – Stand	dard with One or Three line Fax option	
Speed/Compression MH/G3, MMR/G4, JBig Super G3 Fax Send Features Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic cover sheets Priority send Broadcast up to 200 recipients Booklet Scan PSTN Fax Internet Fax LAN Fax Fax Receive Features One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention Fax Forward When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax. Fax Reports Activity report Dial directory Transmission confirmation Pending fax Mailbox Fax Receive Mailboxes Up to 200 password-protected mailboxes			
Fax Send Features Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast up to 200 recipients Booklet Scan PSTN Fax Internet Fax LAN Fax One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention Fax Forward When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax. Fax Reports Activity report Dial directory Transmission confirmation Pending fax Mailbox Up to 200 password-protected mailboxes	Speed/Modem(s)	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.	
Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast up to 200 recipients Booklet Scan PSTN Fax Internet Fax LAN Fax Fax Receive Features One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention Fax Forward When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax. Fax Reports Activity report Dial directory Transmission confirmation Pending fax Mailbox Mailbox Up to 200 password-protected mailboxes	Speed/Compression	MH/G3, MMR/G4, JBig Super G3	
Reduction at reception to fit available paper Junk Fax prevention When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax. Fax Reports Activity report Dial directory Transmission confirmation Pending fax Mailbox Up to 200 password-protected mailboxes Up to 200 password-protected mailboxes	Fax Send Features	Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast up to 200 recipients Booklet Scan PSTN Fax Internet Fax	
routed to an Email, an FTP or SMB location or a Fax. Fax Reports Activity report Dial directory Transmission confirmation Pending fax Mailbox Up to 200 password-protected mailboxes Up to 200 password-protected mailboxes	Fax Receive Features	Reduction at reception to fit available paper	
Dial directory Transmission confirmation Pending fax Mailbox Fax Receive Mailboxes Up to 200 password-protected mailboxes	Fax Forward		
Mailboxes	Fax Reports	Dial directory Transmission confirmation Pending fax	
Auto Dialing Auto redial, Batch send		Up to 200 password-protected mailboxes	
	Auto Dialing	Auto redial, Batch send	

Single Line option	Total of 200 speed dials (single-line option)
omgre time option	Up to 50 dial groups with up to 20 recipients per group (single line option)
Internet Fax (Optiona	ıl) – Standard with One or Three line Fax option
Capability	Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents in black and white sent via email from remote Internet Fax machines or email clients
Maximum Scan Area	297 x 432 mm
Address Directory Access	Downloaded address list (comma-separated file format)
File Formats	TIFF-FX Profiles S, F with G3 MH or G4 MMR
Resolutions	600 x 600 dpi 400 x 400 dpi 200 x 200 dpi 200 x 100 dpi Bit Depth: 1 bit (black and white)
Network Protocols	SMTP POP3
Compliance	ITU-T T.37 compliant
Copy Specifications	
First-Image-Out Time	- A4, from Platen to Centre Tray
Black and White	As fast as 4.8 Seconds
Colour	As fast as 6.7 Seconds
Copying	
Document Scanner	Duplex Automatic Document Feeder with 75-sheet capacity (based on 80 gsm paper)
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi
Concurrency	Concurrent scanning and printing
Digital Imaging	Auto colour Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Colour balance, shift and saturation
Reduction/ Enlargement	Variable zoom from 25 % to 400 % in 1 % increments Anamorphic zoom Six user-programmable percentages

Special Features	Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Auto colour selection Watermark Annotation Area Designation Full colour Single/Dual colour Copy calibration Booklet creation Multi-up – 2, 4 or 8 up Repeat image Transparency dividers Negative image Mirror image Covers insertion (front only, front and back, back only; blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Store and recall job programming Job interrupt Bound document copying Sample set Mixed-size originals Hole Punch (requires Professional Finisher or Advanced Office Finisher) V-Folding (requires Professional Finisher) Stapling (single/dual/quad) quad requires Advanced Office Finisher or Professional Finisher ID Card Copy
Foreign Device Interface	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service
Device Specifications	
Paper Handling – Dup	olex Automatic Document Feeder
Capacity	75 sheets (based on 80 gsm paper)
Speed	50 images per minute black and white / 45 images per minute colour (A4 long edge feed (LEF))
Paper Sizes Sensed	A5/148 x 210 mm long edge feed (LEF) or short edge feed (SEF) A4/210 x 297 mm LEF or SEF 216 x 356 mm SEF A3/297 x 420 mm SEF B5/182 x 257 mm SEF
Weights	38 to 128 gsm
Paper Handling – Byp	ass Tray
Capacity*	100 sheets
Sizes	A6/105 x 148 mm to SRA3/320 x 450 mm
Weights	55 to 220 gsm
Types	Same as front-loading trays plus label stock and envelopes
Paper Handling – From	nt-Loading Paper Tray (Standard)
Capacity*	520 sheets
Sizes	User adjustable from A5/148 x 210 mm to A3/297 x 420 mm
Weights	55 to 220 gsm

Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Heavyweight Gloss Labels Gloss Extra Heavyweight Gloss Punched Letterhead Pre-printed Envelopes	
Paper Handling – Inpu	ut Tray Options - Three Tray Option (Tray One and Two plus Two Tray Module)	
Tray 2 - Tray 4	520 sheets	
Sizes	User adjustable from A5/148 x 210 mm to A3/297 x 420 mm	
Weights	55 to 220 gsm	
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Heavyweight Gloss Labels Gloss Extra Heavyweight Gloss Punched Letterhead Pre-printed Envelopes	
Total Capacity*	2,180 sheets (Includes Tray 1, Tray 2, Trays 3-4 and Bypass Tray)	
Paper Handling – Inpu	Paper Handling – Input Tray Options - High-Capacity Tandem Tray Option	
Tray 2	520 sheets	
Sizes	User adjustable from A5/148 x 210 mm to A3/297 x 420 mm	
Tray 3 - Tray 4	2,000 sheets	

B5, A4

64 to 220 gsm

Sizes Weights

Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Heavyweight Gloss Labels Gloss Extra Heavyweight Gloss Punched Letterhead Pre-printed Envelopes			
Total Capacity*	3,140 sheets (Includes Tray 1, Tray 2, Bypass Tray and High Capacity Feeder)			
Output – Centre Catc	h Tray			
Stacking Tray	400 sheets (Cannot be accessed with the Advanced Office Finisher or Professional Finisher attached)			
Sizes	A6/105 x 148 mm to 320 x 483 mm			
Output – Convenience	e Stapler Option			
Capacity*	Up to 50 sheets (5,000 staples per cartridge)			
Output – Office Finish	Output – Office Finisher Option			
Stacking Tray	1,000 sheets			
Sizes	B5 to A3			
Weights	64 to 105 gsm			
Stapling	Single and dual Auto stapling (50 sheets maximum) – 80 gsm A3, A4, B4 and B5 sizes supported			
Output – Advanced O	Office Finisher Option			
Top Tray	500 sheets			
Stacking Stapling Tray	3,000 sheets			
Sizes	B5 to A3			
Weights	60 to 220 gsm			
Stapling	Single and dual Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported			
Hole Punch	2–4 Hole Punch			
Output – Professiona	l Finisher Option			
Top Tray	500 sheets			
Stacking Stapling Tray	1,500 sheets			
Sizes	B5 to A3			
Weights	60 to 220 gsm			

Stapling	Single Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported			
Booklets - Booklet Tray	Saddle-stitch up to 15 sheets (One 169 gsm cover plus fourteen 90 gsm sheets) V-fold up to 5 sheets A3, A4 supported			
Hole Punch	2–4 Hole Punch			
Security				
Capability	Secure Print, NDS Authentication over IP, LDAP/Kerberos/SMB, Password Protected PDF, Encrypted Disk, Audit Log and Encrypted Scan to Email. Hard disk overwrite immediate or on demand. Secure Web Page via SSL. IPv6			
Accounting				
Auditron	Allows for control of black and white and colour usage by user by feature; copy, print, fax and scan			
Xerox Standard Accounting	Tracking: Copy, Print, Fax and Scan usage Accounting: Up to 1,000 User accounts (User ID); Up to 500 General accounts (Client); Up to 750 Group accounts (Department) Features: Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.			
Colour Access Via Active Directory	Allows the device to be set up so users have unlimited access to black and white copy and print functions. If a user wants to print or copy in colour they must authenticate.			
Accounting Control	Network accounting to enable Alliance Partner Solutions			
Accounting with Third-Party Server Applications	Up-to-the-minute data on how the system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax			
Monthly Duty Cycle				
	150,000			
Basic Configurations*	* *			

Network Multifunction System with network controller and stand Notes: Platen cover, Duplex Automatic Document Feeder is available with all configurations

Accessories

Three Tray Paper Feeder High Capacity Tandem Tray One-line fax with Internet Fax Three-line fax with Internet Fax Fax Server Enablement

Scan Kit

Thumbnail preview

Secure Watermark

Scan to PC Desktop (Professional or SE edition)

Media Print (Print from a USB Thumb drive or media card)

USB/Parallel Port Printing

Office Finisher

Advanced Office Finisher

Professional Finisher

Foreign Device Interface

Convenience Stapler

Network Accounting Enablement

PostScript

Scanner with Platen

Scanner with DADF

Scanner Stand

Mobility Plate

Media Card Reader

Data security

Mini Work Surface

Electrical Requirements

220-240 V Nominal, 50/60 Hz, 10A

Power Consumption	
Running	< 1080 watts
Standby	< 200 watts
Low-Power Mode	< 85 watts
Sleep Mode	< 10 watts
Warm Up	70 seconds
Low-Power Recovery	30 seconds (maximum)
Required Temperature Range	10° to 28° C
Required Relative Humidity	15% to 85%

Noise Emission	28 dB(A) standby 56 dB(A) running 61 dB(A) impulse
Heat Emission	3441 BTU/Hr running 683 BTU/Hr standby

Dimensions and Weight	Width	Depth	Height	Weight
Fully Configured	1,856 mm	834 mm	1,161 mm	280 kg

Xerox Extensible Interface Platform™ (EIP)

Xerox Extensible Interface Platform (EIP) is an embedded software platform built with state of the art web technologies. This platform provides the means for software developers to quickly build solutions that are more intuitive and user-friendly for the office workers. Chief among the capabilities provided by EIP is the development of tailored applications with customised user interfaces, and card-based authentication solutions supporting a personalised user experience.

Certifications

FCC Class B Compliant (U.S.), DOC Class A Compliant (Canada)

89/336/EEC (Europe)

UL Listed (UL60950-1, First Edition) CB Certified (IEC 60950-1/EN 60950-1)

73/23/EEC (Europe)

Novell Tested and Approved Windows Hardware Quality Labs

Supplies	Description	Order Number		
Toner Cartridges	Black Cyan Magenta Yellow	6R1175 6R1176 6R1177 6R1178		
Staple Refills	For Office Finisher	8R12915		
	For Advanced Finisher	8R12941	Used on Advanced and Professional Finisher plus Convenience Stapler 3 refills at 5,000 each	
	For Professional Finisher	8R12925	Used on Professional Finisher (Booklet Function) 4 refills at 5,000 each	
Staple Cartridges	For Advanced and Professional Finishers	8R12964	Used on Advanced and Professional Finisher plus Convenience Stapler (1 cartridge)	
Smart Kits				
	Smart Kit™ Drum Cartridge	13R00624		
	Smart Kit™ Waste Cartridge	8R12903		
	Smart Kit™ Fuser Module (220 V)	8R13056		











